











	MODEL NUMBER	PRODUCT	W	D	H	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
	EL-AS	Atlas Stand	30 ¹ / ₂ "	29"	44 ¹ / ₂ "	260 Lbs.	30 Cu Ft	\$ 3,285	<p>CONSTRUCTION ASSEMBLY: A ³/₄" thick particleboard core back complete with grade "A" veneer faces shall be attached to the end panels by means of hidden key-hole fasteners. The top will be fastened to the end panels and back by means of male and female beta clips. The unit will accommodate five pull-out shelves operating on blum slides. Shelves will be constructed of ³/₄" thick plywood with grade "A" veneer faces and the front edge banded with a ³/₄" thick x 1³/₄" high solid retainer lip.</p> <p>TOP: Sloped top assembly shall be constructed from ³/₄" thick high density particleboard core, assembled by means of tongue and groove. All surfaces of top to be laminated with a .050" thick laminate. Top will be fitted with a book support rail ⁵/₈" thick x ⁵/₈" deep.</p> <p>END PANEL FRAME ASSEMBLY: End panels shall be constructed 1⁵/₈" thick, consisting of a 1" thick 3 ply particleboard core with plain sliced veneer both faces. Panels are miter framed on four sides with 1⁵/₈" thick x 2¹/₂" wide solid hardwood. The panel will then be fitted with two ¹/₂" wide x ¹/₂" thick steel bars inset between vertical solid frame members. All edges of panel frame will be eased.</p> <p>GLIDES: Each leg will be fitted with a threaded T-nut to accept a 1¹/₈" diameter cushioned glide with a 1" x ³/₈" threaded stem.</p>



	MODEL NUMBER	PRODUCT	W	D	H	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
	EL-DC	Dictionary Stand	27 ¹ / ₂ "	21"	44 ¹ / ₄ "	180 Lbs.	20 Cu Ft	\$ 2,415	<p>CONSTRUCTION ASSEMBLY: A ³/₄" thick particleboard core back complete with grade "A" veneer faces shall be attached to the end panels by means of hidden key-hole fasteners. The top will be fastened to the end panels and back by means of male and female beta clips. The unit will come complete with one shelf and a fixed bottom, constructed from ³/₄" thick plywood with grade "A" veneer on both faces, front edge of shelf banded with a ¹/₄" thick solid hardwood. Shelf will be adjustable on 1 ¹/₄" increments. The fixed bottom shelf will have a ³/₄" x 1 ³/₄" drop edge mounted to the front edge.</p> <p>TOP: Sloped top assembly shall be constructed from ³/₄" thick high density particleboard core, assembled by means of tongue and groove. All surfaces of top to be laminated with a .050" thick laminate. Top will be fitted with a book support rail ⁵/₈" thick x ⁵/₈" deep.</p> <p>END PANEL FRAME ASSEMBLY: End panels shall be constructed 1 ⁵/₈" thick, consisting of a 1" thick 3 ply particleboard core with plain sliced veneer both faces. Panels are miter framed on four sides with 1 ⁵/₈" thick x 2 ¹/₂" wide solid hardwood. The panel will then be fitted with two ¹/₂" wide x ¹/₂" thick steel bars inset between vertical solid frame members. All edges of panel frame will be eased.</p> <p>GLIDES: Each leg will be fitted with a threaded T-nut to accept a 1 ¹/₈" diameter cushioned glide with a 1" x ³/₈" threaded stem.</p>



	MODEL NUMBER	PRODUCT	W	D	H	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
	EL-MC-36-SS	Single Face Modular Carrels: 36" Starter	37 ¹ / ₂ "	31"	48"	340 Lbs.	11 Cu Ft	\$ 2,310	CARREL TOP: Carrel top shall be constructed of 1 ¹ / ₄ " thick 3 ply particleboard core. Top surface to be laminated with a .050" thick high pressure laminate sheet, bottom surface laminated with a backing sheet not less than .020" thick. Front edge shall receive a 1 ¹ / ₄ " x 1 ¹ / ₄ " solid external hardwood edge, complete with a 5" wide plastic laminate strip. Edge banded to top after top and bottom laminate sheets have been applied. Top shall be secured to end panels and back by means of machine bolts passing through a 1 ¹ / ₂ " x 1 ¹ / ₂ " steel flange into inserts embedded in the panels. Top will receive a 1 ¹ / ₃₂ " V-groove detail where laminate and solid edge meet. Worksurface 28" deep.
	EL-MC-36-SA	36" Adder	36 ¹ / ₄ "	31"	48"	165 Lbs.	11 Cu Ft	\$ 1,845	
	EL-MC-48-SS	48" Starter	49 ¹ / ₂ "	31"	48"	370 Lbs.	11 Cu Ft	\$ 2,370	
	EL-MC-48-SA	48" Adder	48 ¹ / ₄ "	31"	48"	200 Lbs.	11 Cu Ft	\$ 1,905	
	EL-MC-36-DS	Double Face Modular Carrels: 36" Starter	37 ¹ / ₂ "	60 ¹ / ₂ "	48"	715 Lbs.	22 Cu Ft	\$ 3,365	END PANEL FRAME ASSEMBLY: End panels shall be constructed 1 ⁵ / ₈ " thick, consisting of a 1" thick 3 ply particleboard core with plain sliced veneer both faces. Panels are miter framed on four sides with 1 ⁵ / ₈ " thick x 1 ¹ / ₂ " wide solid hardwood. The panel will then be fitted with two 1 ¹ / ₂ " wide x 1 ¹ / ₂ " thick steel bars inset between two vertical solid frame members. All edges of the panel frame are eased. MID PANELS: Intermediate panels shall be constructed from 1 ¹ / ₄ " thick high density particleboard veneered on both faces with grade "A" veneer. All four edges are miter banded with 1 ¹ / ₄ " x 1 ¹ / ₂ " solid hardwood. All edges will be eased. BACK PANEL: Constructed from 1" thick particleboard core with plain sliced grade "A" veneer both faces. Top edge is banded with a 1" x 1 ¹ / ₄ " solid hardwood, edges eased. Back panel will be fastened to end panels by means of hidden key-hole fasteners and pin assembly. Panel will sit 2" above the floor. GLIDES: Each leg will be fitted with a threaded T-nut to accept a 1 ¹ / ₈ " diameter cushioned glide with a 1" x 3 ³ / ₈ " threaded stem. SHELF: Constructed from 3 ³ / ₄ " thick particleboard core with grade "A" veneer on both faces. The front edge shall be banded with 1 ¹ / ₄ " external hardwood. Shelf is 9" deep positioned 16 ¹ / ₄ " above the worksurface. Shelf will be mounted to the side panels by means of hidden keyhole fasteners. WORKSURFACE: Standard worksurface height shall be 29" high. Optional heights of 32" - wheelchair, 27" and 25" may be specified at no additional upcharge. OPTION: Electrical components - see electrical section in Palmieri Furniture spec book.
	EL-MC-36-DA	36" Adder	36 ¹ / ₄ "	60 ¹ / ₂ "	48"	250 Lbs.	22 Cu Ft	\$ 2,495	
	EL-MC-48-DS	48" Starter	49 ¹ / ₂ "	60 ¹ / ₂ "	48"	715 Lbs.	22 Cu Ft	\$ 3,460	
	EL-MC-48-DA	48" Adder	48 ¹ / ₄ "	60 ¹ / ₂ "	48"	310 Lbs.	22 Cu Ft	\$ 2,590	



	MODEL NUMBER	PRODUCT	W	D	H		WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
		Single Face Reference Carrels:								
	EL-RC-36-SS	36" Starter	37 ¹ / ₂ "	31"	48"		340 Lbs.	11 Cu Ft	\$ 2,445	CARREL TOP: Carrel top shall be constructed of 1 ¹ / ₄ " thick 3 ply particleboard core. Top surface to be laminated with a .050" thick high pressure laminate sheet, bottom surface laminated with a backing sheet not less than .020" thick. Front edge shall receive a 1/4" x 1 ¹ / ₄ " solid external hardwood edge, complete with a 5" wide plastic laminate strip. Edge banded to top after top and bottom laminate sheets have been applied. Top will be set back from the back panel 2" to provide a wire management drop. Back edge of top will be fitted with a retainer lip. Top shall be secured to end panels by means of machine bolts passing through a 1 ¹ / ₂ " x 1 ¹ / ₂ " steel flange into inserts embedded in the panels. Top will receive a 1/32" V-groove detail where laminate and solid edge meet. Work surface 26" deep.
	EL-RC-36-SA	36" Adder	36 ¹ / ₄ "	31"	48"		165 Lbs.	11 Cu Ft	\$ 1,980	
	EL-RC-48-SS	48" Starter	49 ¹ / ₂ "	31"	48"		370 Lbs.	11 Cu Ft	\$ 2,500	
	EL-RC-48-SA	48" Adder	48 ¹ / ₄ "	31"	48"		200 Lbs.	11 Cu Ft	\$ 2,035	
		Double Face Reference Carrels:								
	EL-RC-36-DS	36" Starter	37 ¹ / ₂ "	60 ¹ / ₂ "	48"		715 Lbs.	22 Cu Ft	\$ 3,630	END PANEL FRAME ASSEMBLY: End panels shall be constructed 1 ⁵ / ₈ " thick, consisting of a 1" thick 3 ply particleboard core with plain sliced veneer both faces. Panels are miter framed on four sides with 1 ⁵ / ₈ " thick x1 ¹ / ₂ " wide solid hardwood. The panel will then be fitted with two 1/2" wide x 1/2" thick steel bars inset between two vertical solid frame members. All edges of the panel frame are eased.
	EL-RC-36-DA	36" Adder	36 ¹ / ₄ "	60 ¹ / ₂ "	48"		250 Lbs.	22 Cu Ft	\$ 2,760	
	EL-RC-48-DS	48" Starter	49 ¹ / ₂ "	60 ¹ / ₂ "	48"		715 Lbs.	22 Cu Ft	\$ 3,725	
	EL-RC-48-DA	48" Adder	48 ¹ / ₄ "	60 ¹ / ₂ "	48"		310 Lbs.	22 Cu Ft	\$ 2,855	
MID PANELS: Intermediate panels shall be constructed from 1 ¹ / ₄ " thick high density particleboard veneered on both faces with grade "A" veneer. All four edges are miter banded with 1 ¹ / ₄ " x1 ¹ / ₂ " solid hardwood. All edges are eased.										
BACK PANEL: Constructed from 1" thick particleboard core with plain sliced grade "A" veneer both faces. Top edge is banded with a 1" x 1 ¹ / ₂ " solid hardwood, edges eased. Back panel will be fastened to end panels by means of hidden key-hole fasteners and pin assembly. Panel will sit 2" above the floor.										
GLIDES: Each leg will be fitted with a threaded T-nut to accept a 1 ¹ / ₈ " diameter cushioned glide with a 1" x ³ / ₈ " threaded stem.										
SHELF: Located below the work surface. Constructed from ³ / ₄ " thick particleboard core with grade "A" veneer on both faces. The front edge shall be banded with 1/4" solid external hardwood edge. Shelf is 9" deep positioned 21" above the floor. Shelf will be mounted to the side panels by means of machine bolts passing through a 1 ¹ / ₂ " x 1 ¹ / ₂ " steel flange into inserts imbedded in the end panels.										
WORKSURFACE: Work surface heights adjustable at four increments 39", 32", 29" and 27".										
OPTION: Electrical components - see electrical section in Palmieri Specification book										



	MODEL NUMBER	PRODUCT	W	D	H	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
	1 Person PAC Tables:								SUPERSTRUCTURE: Side panels, mid panels and back panel shall be constructed from 3/4" veneer plywood complete with 1/4" banding. All edges and corners shall be eased. The side panels shall be tapered down from a top dimension of 5 1/2" wide to 7" wide at the bottom. Racks shall be 8" high and 7" deep. The rack is mounted to top by means of wood screws passing through the underside of the top and into the rack. TABLE TOP: Table tops shall be constructed of 1 1/4" thick 3 ply particleboard core. Top surface to be laminated with a .050" thick high pressure plastic laminate sheet. Bottom surface to be laminated with a backing sheet not less than .020" thick. Surrounding edges shall receive a 1/4" x 1 1/4" solid external hardwood edge. Edges shall be applied to top after the top and bottom laminate sheets have been applied. The front long edge of the work surface shall receive a 5" wide plastic laminate strip. Tops shall receive a 1/32" v-groove detail where laminate and solid meet. TABLE TOP SUPPORTS: All tables 60" and longer shall be fitted with a v-shaped, 14 gauge steel keel. The keel shall be mounted to the underside of the top by means of wood screws. All tables 48" wide and 60" long and longer shall be fitted with two parallel steel keels LEG ASSEMBLY: Legs are 2 3/8" x 2 3/8" glued up solid stock. The two inside edges are tapered down to 1 1/2" x 1 1/2". The leg is attached to a metal plate by means of two threaded machine bolts fastened to a barrel nut embedded in the leg. Two steel decorative angle bars are attached to the upper outside corners of the leg spaced 5" apart. LEG PLATE: Corner leg plates shall be 5" x 5" x 1/4" powder epoxy coated steel plate. The two inside corners of the plate shall have a fin angled design incorporating support to the leg. GLIDES: Each leg will be fitted with a threaded T-nut to accept a 1 5/8" diameter cushioned glide with a 1 1/2" x 3/8" threaded stem. WORK SURFACE HEIGHT: Standard work surface height shall be 39" high - standing, 29" high - sitting, 32" high - wheelchair. Optional heights of 27" and 25" may be specified at no additional up-charge. ELECTRICAL ACCESSORIES: Each table shall receive 3" diameter black plastic grommets and a black steel J-channel for wire management. The J-channel will be mounted to the underside of the top by means of wood screws.
	EL-PAC-1-29-W	Sitting Height, Wood Divider	36"	36"	37"	65 Lbs.	10 Cu Ft	\$ 2,890	
	EL-PAC-1-29-A	Sitting Height, Acrylic Divider	36"	36"	37"	65 Lbs.	10 Cu Ft	\$ 3,040	
	EL-PAC-1-32-W	Wheelchair Height, Wood Divider	36"	36"	40"	65 Lbs.	10 Cu Ft	\$ 2,935	
	EL-PAC-1-32-A	Wheelchair Height, Acrylic Divider	36"	36"	40"	65 Lbs.	10 Cu Ft	\$ 3,085	
	EL-PAC-1-39-W	Standing Height, Wood Divider	36"	36"	47"	67 Lbs.	10 Cu Ft	\$ 2,965	
	EL-PAC-1-39-A	Standing Height, Acrylic Divider	36"	36"	47"	67 Lbs.	10 Cu Ft	\$ 3,120	
	2 Person (1 Place Back to Back) PAC Tables:								
	EL-PAC-1D-29-W	Sitting Height, Wood Divider	36"	48"	37"	65 Lbs.	10 Cu Ft	\$ 3,005	LEG ASSEMBLY: Legs are 2 3/8" x 2 3/8" glued up solid stock. The two inside edges are tapered down to 1 1/2" x 1 1/2". The leg is attached to a metal plate by means of two threaded machine bolts fastened to a barrel nut embedded in the leg. Two steel decorative angle bars are attached to the upper outside corners of the leg spaced 5" apart. LEG PLATE: Corner leg plates shall be 5" x 5" x 1/4" powder epoxy coated steel plate. The two inside corners of the plate shall have a fin angled design incorporating support to the leg. GLIDES: Each leg will be fitted with a threaded T-nut to accept a 1 5/8" diameter cushioned glide with a 1 1/2" x 3/8" threaded stem. WORK SURFACE HEIGHT: Standard work surface height shall be 39" high - standing, 29" high - sitting, 32" high - wheelchair. Optional heights of 27" and 25" may be specified at no additional up-charge. ELECTRICAL ACCESSORIES: Each table shall receive 3" diameter black plastic grommets and a black steel J-channel for wire management. The J-channel will be mounted to the underside of the top by means of wood screws.
	EL-PAC-1D-29-A	Sitting Height, Acrylic Divider	36"	48"	37"	65 Lbs.	10 Cu Ft	\$ 3,195	
	EL-PAC-1D-32-W	Wheelchair Height, Wood Divider	36"	48"	40"	65 Lbs.	10 Cu Ft	\$ 3,050	
	EL-PAC-1D-32-A	Wheelchair Height, Acrylic Divider	36"	48"	40"	65 Lbs.	10 Cu Ft	\$ 3,240	
	EL-PAC-1D-39-W	Standing Height, Wood Divider	36"	48"	47"	67 Lbs.	10 Cu Ft	\$ 3,130	
	EL-PAC-1D-39-A	Standing Height, Acrylic Divider	36"	48"	47"	67 Lbs.	10 Cu Ft	\$ 3,320	




	MODEL NUMBER	PRODUCT	W	D	H	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
	2 Person PAC Tables:								SUPERSTRUCTURE: Side panels, mid panels and back panel shall be constructed from 3/4" veneer plywood complete with 1/4" banding. All edges and corners shall be eased. The side panels shall be tapered down from a top dimension of 5 1/2" wide to 7" wide at the bottom. Racks shall be 8" high and 7" deep. The rack is mounted to top by means of wood screws passing through the underside of the top and into the rack. TABLE TOP: Table tops shall be constructed of 1 1/4" thick 3 ply particleboard core. Top surface to be laminated with a .050" thick high pressure plastic laminate sheet. Bottom surface to be laminated with a backing sheet not less than .020" thick. Surrounding edges shall receive a 1/4" x 1 1/4" solid external hardwood edge. Edges shall be applied to top after the top and bottom laminate sheets have been applied. The front long edge of the work surface shall receive a 5" wide plastic laminate strip. Tops shall receive a 1/32" v-groove detail where laminate and solid meet. TABLE TOP SUPPORTS: All tables 60" and longer shall be fitted with a v-shaped, 14 gauge steel keel. The keel shall be mounted to the underside of the top by means of wood screws. All tables 48" wide and 60" long and longer shall be fitted with two parallel steel keels LEG ASSEMBLY: Legs are 2 3/8" x 2 3/8" glued up solid stock. The two inside edges are tapered down to 1 1/2" x 1 1/2". The leg is attached to a metal plate by means of two threaded machine bolts fastened to a barrel nut embedded in the leg. Two steel decorative angle bars are attached to the upper outside corners of the leg spaced 5" apart. LEG PLATE: Corner leg plates shall be 5" x 5" x 1/4" powder epoxy coated steel plate. The two inside corners of the plate shall have a fin angled design incorporating support to the leg. GLIDES: Each leg will be fitted with a threaded T-nut to accept a 1 5/8" diameter cushioned glide with a 1 1/2" x 3/8" threaded stem. WORK SURFACE HEIGHT: Standard work surface height shall be 39" high - standing, 29" high - sitting, 32" high - wheelchair. Optional heights of 27" and 25" may be specified at no additional up-charge. ELECTRICAL ACCESSORIES: Each table shall receive 3" diameter black plastic grommets and a black steel J-channel for wire management. The J-channel will be mounted to the underside of the top by means of wood screws.
	EL-PAC-2-29-W	Sitting Height, Wood Divider	72"	36"	37"	100 Lbs.	21 Cu Ft	\$ 3,225	
	EL-PAC-2-29-A	Sitting Height, Acrylic Divider	72"	36"	37"	100 Lbs.	21 Cu Ft	\$ 3,700	
	EL-PAC-2-32-W	Wheelchair Height, Wood Divider	72"	36"	40"	100 Lbs.	21 Cu Ft	\$ 3,270	
	EL-PAC-2-32-A	Wheelchair Height, Acrylic Divider	72"	36"	40"	100 Lbs.	21 Cu Ft	\$ 3,745	
	EL-PAC-2-39-W	Standing Height, Wood Divider	72"	36"	47"	100 Lbs.	21 Cu Ft	\$ 3,375	
	EL-PAC-2-39-A	Standing Height, Acrylic Divider	72"	36"	47"	100 Lbs.	21 Cu Ft	\$ 3,850	
	4 Person (2 Place Back to Back) PAC Tables:								
	EL-PAC-2D-29-W	Sitting Height, Wood Divider	72"	48"	37"	100 Lbs.	21 Cu Ft	\$ 3,630	
	EL-PAC-2D-29-A	Sitting Height, Acrylic Divider	72"	48"	37"	100 Lbs.	21 Cu Ft	\$ 4,010	
	EL-PAC-2D-32-W	Wheelchair Height, Wood Divider	72"	48"	40"	100 Lbs.	21 Cu Ft	\$ 3,675	
	EL-PAC-2D-32-A	Wheelchair Height, Acrylic Divider	72"	48"	40"	100 Lbs.	21 Cu Ft	\$ 4,055	
	EL-PAC-2D-39-W	Standing Height, Wood Divider	72"	48"	47"	100 Lbs.	21 Cu Ft	\$ 3,750	
	EL-PAC-2D-39-A	Standing Height, Acrylic Divider	72"	48"	47"	100 Lbs.	21 Cu Ft	\$ 4,130	

	MODEL NUMBER	PRODUCT	W	D	H	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
	3 Person PAC Tables:								SUPERSTRUCTURE: Side panels, mid panels and back panel shall be constructed from 3/4" veneer plywood complete with 1/4" banding. All edges and corners shall be eased. The side panels shall be tapered down from a top dimension of 5 1/2" wide to 7" wide at the bottom. Racks shall be 8" high and 7" deep. The rack is mounted to top by means of wood screws passing through the underside of the top and into the rack. TABLE TOP: Table tops shall be constructed of 1 1/4" thick 3 ply particleboard core. Top surface to be laminated with a .050" thick high pressure plastic laminate sheet. Bottom surface to be laminated with a backing sheet not less than .020" thick. Surrounding edges shall receive a 1/4" x 1 1/4" solid external hardwood edge. Edges shall be applied to top after the top and bottom laminate sheets have been applied. The front long edge of the work surface shall receive a 5" wide plastic laminate strip. Tops shall receive a 1/32" v-groove detail where laminate and solid meet. TABLE TOP SUPPORTS: All tables 60" and longer shall be fitted with a v-shaped, 14 gauge steel keel. The keel shall be mounted to the underside of the top by means of wood screws. All tables 48" wide and 60" long and longer shall be fitted with two parallel steel keels LEG ASSEMBLY: Legs are 2 3/8" x 2 3/8" glued up solid stock. The two inside edges are tapered down to 1 1/2" x 1 1/2". The leg is attached to a metal plate by means of two threaded machine bolts fastened to a barrel nut embedded in the leg. Two steel decorative angle bars are attached to the upper outside corners of the leg spaced 5" apart. LEG PLATE: Corner leg plates shall be 5" x 5" x 1/4" powder epoxy coated steel plate. The two inside corners of the plate shall have a fin angled design incorporating support to the leg. GLIDES: Each leg will be fitted with a threaded T-nut to accept a 1 5/8" diameter cushioned glide with a 1 1/2" x 3/8" threaded stem. WORK SURFACE HEIGHT: Standard work surface height shall be 39" high - standing, 29" high - sitting, 32" high - wheelchair. Optional heights of 27" and 25" may be specified at no additional up-charge. ELECTRICAL ACCESSORIES: Each table shall receive 3" diameter black plastic grommets and a black steel J-channel for wire management. The J-channel will be mounted to the underside of the top by means of wood screws.
	EL-PAC-3-29-W	Sitting Height, Wood Divider	90"	36"	37"	110 Lbs.	26 Cu Ft	\$ 3,405	
	EL-PAC-3-29-A	Sitting Height, Acrylic Divider	90"	36"	37"	110 Lbs.	26 Cu Ft	\$ 4,225	
	EL-PAC-3-32-W	Wheelchair Height, Wood Divider	90"	36"	40"	110 Lbs.	26 Cu Ft	\$ 3,450	
	EL-PAC-3-32-A	Wheelchair Height, Acrylic Divider	90"	36"	40"	110 Lbs.	26 Cu Ft	\$ 4,270	
	EL-PAC-3-39-W	Standing Height, Wood Divider	90"	36"	47"	114 Lbs.	26 Cu Ft	\$ 3,625	
	EL-PAC-3-39-A	Standing Height, Acrylic Divider	90"	36"	47"	114 Lbs.	26 Cu Ft	\$ 4,440	
	6 Person (3 Place Back to Back) PAC Tables:								
	EL-PAC-3D-29-W	Sitting Height, Wood Divider	90"	48"	37"	110 Lbs.	26 Cu Ft	\$ 3,880	
	EL-PAC-3D-29-A	Sitting Height, Acrylic Divider	90"	48"	37"	110 Lbs.	26 Cu Ft	\$ 4,610	
	EL-PAC-3D-32-W	Wheelchair Height, Wood Divider	90"	48"	40"	110 Lbs.	26 Cu Ft	\$ 3,925	
	EL-PAC-3D-32-A	Wheelchair Height, Acrylic Divider	90"	48"	40"	110 Lbs.	26 Cu Ft	\$ 4,655	
	EL-PAC-3D-39-W	Standing Height, Wood Divider	90"	48"	47"	114 Lbs.	26 Cu Ft	\$ 4,070	
	EL-PAC-3D-39-A	Standing Height, Acrylic Divider	90"	48"	47"	114 Lbs.	26 Cu Ft	\$ 4,800	

	MODEL NUMBER	PRODUCT	W	D	H	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
	1 Person PAC Tables, Panel Base:								SUPERSTRUCTURE: Side panels, mid panels and back panel shall be constructed from 3/4" veneer plywood complete with 1/4" banding. All edges and corners shall be eased. The side panels shall be tapered down from a top dimension of 5 1/2" wide to 7" wide at the bottom. Racks shall be 8" high and 7" deep. The rack is mounted to top by means of wood screws passing through the underside of the top and into the rack. TABLE TOP: Table tops shall be constructed of 1 1/4" thick 3 ply particleboard core. Top surface to be laminated with a .050" thick high pressure plastic laminate sheet. Bottom surface to be laminated with a backing sheet not less than .020" thick. Surrounding edges shall receive a 1/4" x 1 1/4" solid external hardwood edge. Edges shall be applied to top after the top and bottom laminate sheets have been applied. The front long edge of the work surface shall receive a 5" wide plastic laminate strip. Tops shall receive a 1/32" v-groove detail where laminate and solid meet.
	EL-PAC-1-PB-29-W	Sitting Height, Wood Divider	36"	36"	37"	65 Lbs.	10 Cu Ft	\$ 2,215	
	EL-PAC-1-PB-29-A	Sitting Height, Acrylic Divider	36"	36"	37"	65 Lbs.	10 Cu Ft	\$ 2,510	
	EL-PAC-1-PB-32-W	Wheelchair Height, Wood Divider	36"	36"	40"	65 Lbs.	10 Cu Ft	\$ 2,225	
	EL-PAC-1-PB-32-A	Wheelchair Height, Acrylic Divider	36"	36"	40"	65 Lbs.	10 Cu Ft	\$ 2,520	
	EL-PAC-1-PB-39-W	Standing Height, Wood Divider	36"	36"	47"	67 Lbs.	10 Cu Ft	\$ 2,260	
	EL-PAC-1-PB-39-A	Standing Height, Acrylic Divider	36"	36"	47"	67 Lbs.	10 Cu Ft	\$ 2,555	
	2 Person (1 Place Back to Back) PAC Tables, Panel Base:								TABLE TOP SUPPORTS: All tables 60" and longer shall be fitted with a v-shaped, 14 gauge steel keel. The keel shall be mounted to the underside of the top by means of wood screws. All tables 48" wide and 60" long and longer shall be fitted with two parallel steel keels LEG ASSEMBLY: Legs are 2 3/8" x 2 3/8" glued up solid stock. The two inside edges are tapered down to 1 1/2" x 1 1/2". The leg is attached to a metal plate by means of two threaded machine bolts fastened to a barrel nut embedded in the leg. Two steel decorative angle bars are attached to the upper outside corners of the leg spaced 5" apart. LEG PLATE: Corner leg plates shall be 5" x 5" x 1/4" powder epoxy coated steel plate. The two inside corners of the plate shall have a fin angled design incorporating support to the leg. GLIDES: Each leg will be fitted with a threaded T-nut to accept a 1 5/8" diameter cushioned glide with a 1 1/2" x 3/8" threaded stem. WORK SURFACE HEIGHT: Standard work surface height shall be 39" high - standing, 29" high - sitting, 32" high - wheelchair. Optional heights of 27" and 25" may be specified at no additional up-charge. ELECTRICAL ACCESSORIES: Each table shall receive 3" diameter black plastic grommets and a black steel J-channel for wire management. The J-channel will be mounted to the underside of the top by means of wood screws.
	EL-PAC-1D-PB-29-W	Sitting Height, Wood Divider	36"	48"	37"	65 Lbs.	10 Cu Ft	\$ 2,560	
	EL-PAC-1D-PB-29-A	Sitting Height, Acrylic Divider	36"	48"	37"	65 Lbs.	10 Cu Ft	\$ 2,890	
	EL-PAC-1D-PB-32-W	Wheelchair Height, Wood Divider	36"	48"	40"	65 Lbs.	10 Cu Ft	\$ 2,575	
	EL-PAC-1D-PB-32-A	Wheelchair Height, Acrylic Divider	36"	48"	40"	65 Lbs.	10 Cu Ft	\$ 2,905	
	EL-PAC-1D-PB-39-W	Standing Height, Wood Divider	36"	48"	47"	67 Lbs.	10 Cu Ft	\$ 2,600	
		EL-PAC-1D-PB-39-A	Standing Height, Acrylic Divider	36"	48"	47"	67 Lbs.	10 Cu Ft	\$ 2,935

	MODEL NUMBER	PRODUCT	W	D	H	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
	2 Person PAC Tables, Panel Base:								SUPERSTRUCTURE: Side panels, mid panels and back panel shall be constructed from 3/4" veneer plywood complete with 1/4" banding. All edges and corners shall be eased. The side panels shall be tapered down from a top dimension of 5 1/2" wide to 7" wide at the bottom. Racks shall be 8" high and 7" deep. The rack is mounted to top by means of wood screws passing through the underside of the top and into the rack. TABLE TOP: Table tops shall be constructed of 1 1/4" thick 3 ply particleboard core. Top surface to be laminated with a .050" thick high pressure plastic laminate sheet. Bottom surface to be laminated with a backing sheet not less than .020" thick. Surrounding edges shall receive a 1/4" x 1 1/4" solid external hardwood edge. Edges shall be applied to top after the top and bottom laminate sheets have been applied. The front long edge of the work surface shall receive a 5" wide plastic laminate strip. Tops shall receive a 1/32" v-groove detail where laminate and solid meet. TABLE TOP SUPPORTS: All tables 60" and longer shall be fitted with a v-shaped, 14 gauge steel keel. The keel shall be mounted to the underside of the top by means of wood screws. All tables 48" wide and 60" long and longer shall be fitted with two parallel steel keels LEG ASSEMBLY: Legs are 2 3/8" x 2 3/8" glued up solid stock. The two inside edges are tapered down to 1 1/2" x 1 1/2". The leg is attached to a metal plate by means of two threaded machine bolts fastened to a barrel nut embedded in the leg. Two steel decorative angle bars are attached to the upper outside corners of the leg spaced 5" apart. LEG PLATE: Corner leg plates shall be 5" x 5" x 1/4" powder epoxy coated steel plate. The two inside corners of the plate shall have a fin angled design incorporating support to the leg. GLIDES: Each leg will be fitted with a threaded T-nut to accept a 1 5/8" diameter cushioned glide with a 1 1/2" x 3/8" threaded stem. WORK SURFACE HEIGHT: Standard work surface height shall be 39" high - standing, 29" high - sitting, 32" high - wheelchair. Optional heights of 27" and 25" may be specified at no additional up-charge. ELECTRICAL ACCESSORIES: Each table shall receive 3" diameter black plastic grommets and a black steel J-channel for wire management. The J-channel will be mounted to the underside of the top by means of wood screws.
	EL-PAC-2-PB-29-W	Sitting Height, Wood Divider	72"	36"	37"	100 Lbs.	21 Cu Ft	\$ 2,425	
	EL-PAC-2-PB-29-A	Sitting Height, Acrylic Divider	72"	36"	37"	100 Lbs.	21 Cu Ft	\$ 3,040	
	EL-PAC-2-PB-32-W	Wheelchair Height, Wood Divider	72"	36"	40"	100 Lbs.	21 Cu Ft	\$ 2,435	
	EL-PAC-2-PB-32-A	Wheelchair Height, Acrylic Divider	72"	36"	40"	100 Lbs.	21 Cu Ft	\$ 3,050	
	EL-PAC-2-PB-39-W	Standing Height, Wood Divider	72"	36"	47"	100 Lbs.	21 Cu Ft	\$ 2,465	
	4 Person (2 Place Back to Back) PAC Tables, Panel Base:								
	EL-PAC-2D-PB-29-W	Sitting Height, Wood Divider	72"	48"	37"	100 Lbs.	21 Cu Ft	\$ 2,840	
	EL-PAC-2D-PB-29-A	Sitting Height, Acrylic Divider	72"	48"	37"	100 Lbs.	21 Cu Ft	\$ 3,525	
	EL-PAC-2D-PB-32-W	Wheelchair Height, Wood Divider	72"	48"	40"	100 Lbs.	21 Cu Ft	\$ 2,855	
	EL-PAC-2D-PB-32-A	Wheelchair Height, Acrylic Divider	72"	48"	40"	100 Lbs.	21 Cu Ft	\$ 3,540	
	EL-PAC-2D-PB-39-W	Standing Height, Wood Divider	72"	48"	47"	100 Lbs.	21 Cu Ft	\$ 2,885	
	EL-PAC-2D-PB-39-A	Standing Height, Acrylic Divider	72"	48"	47"	100 Lbs.	21 Cu Ft	\$ 3,565	

	MODEL NUMBER	PRODUCT	W	D	H	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
	3 Person PAC Tables, Panel Base:								SUPERSTRUCTURE: Side panels, mid panels and back panel shall be constructed from 3/4" veneer plywood complete with 1/4" banding. All edges and corners shall be eased. The side panels shall be tapered down from a top dimension of 5 1/2" wide to 7" wide at the bottom. Racks shall be 8" high and 7" deep. The rack is mounted to top by means of wood screws passing through the underside of the top and into the rack.
	EL-PAC-3-PB-29-W	Sitting Height, Wood Divider	90"	36"	37"	110 Lbs.	26 Cu Ft	\$ 2,580	
	EL-PAC-3-PB-29-A	Sitting Height, Acrylic Divider	90"	36"	37"	110 Lbs.	26 Cu Ft	\$ 3,540	
	EL-PAC-3-PB-32-W	Wheelchair Height, Wood Divider	90"	36"	40"	110 Lbs.	26 Cu Ft	\$ 2,585	
	EL-PAC-3-PB-32-A	Wheelchair Height, Acrylic Divider	90"	36"	40"	110 Lbs.	26 Cu Ft	\$ 3,545	
	EL-PAC-3-PB-39-W	Standing Height, Wood Divider	90"	36"	47"	114 Lbs.	26 Cu Ft	\$ 2,620	
	EL-PAC-3-PB-39-A	Standing Height, Acrylic Divider	90"	36"	47"	114 Lbs.	26 Cu Ft	\$ 3,580	TABLE TOP: Table tops shall be constructed of 1 1/4" thick 3 ply particleboard core. Top surface to be laminated with a .050" thick high pressure plastic laminate sheet. Bottom surface to be laminated with a backing sheet not less than .020" thick. Surrounding edges shall receive a 1/4" x 1 1/4" solid external hardwood edge. Edges shall be applied to top after the top and bottom laminate sheets have been applied. The front long edge of the work surface shall receive a 5" wide plastic laminate strip. Tops shall receive a 1/32" v-groove detail where laminate and solid meet.
	6 Person (3 Place Back to Back) PAC Tables, Panel Base:								TABLE TOP SUPPORTS: All tables 60" and longer shall be fitted with a v-shaped, 14 gauge steel keel. The keel shall be mounted to the underside of the top by means of wood screws. All tables 48" wide and 60" long and longer shall be fitted with two parallel steel keels
	EL-PAC-3D-PB-29-W	Sitting Height, Wood Divider	90"	48"	37"	110 Lbs.	26 Cu Ft	\$ 3,225	
	EL-PAC-3D-PB-29-A	Sitting Height, Acrylic Divider	90"	48"	37"	110 Lbs.	26 Cu Ft	\$ 4,240	
	EL-PAC-3D-PB-32-W	Wheelchair Height, Wood Divider	90"	48"	40"	110 Lbs.	26 Cu Ft	\$ 3,240	
	EL-PAC-3D-PB-32-A	Wheelchair Height, Acrylic Divider	90"	48"	40"	110 Lbs.	26 Cu Ft	\$ 4,255	
	EL-PAC-3D-PB-39-W	Standing Height, Wood Divider	90"	48"	47"	114 Lbs.	26 Cu Ft	\$ 3,270	
	EL-PAC-3D-PB-39-A	Standing Height, Acrylic Divider	90"	48"	47"	114 Lbs.	26 Cu Ft	\$ 4,280	LEG ASSEMBLY: Legs are 2 3/8" x 2 3/8" glued up solid stock. The two inside edges are tapered down to 1 1/2" x 1 1/2". The leg is attached to a metal plate by means of two threaded machine bolts fastened to a barrel nut embedded in the leg. Two steel decorative angle bars are attached to the upper outside corners of the leg spaced 5" apart.
LEG PLATE: Corner leg plates shall be 5" x 5" x 1/4" powder epoxy coated steel plate. The two inside corners of the plate shall have a fin angled design incorporating support to the leg.									
GLIDES: Each leg will be fitted with a threaded T-nut to accept a 1 5/8" diameter cushioned glide with a 1 1/2" x 3/8" threaded stem.									
WORK SURFACE HEIGHT: Standard work surface height shall be 39" high - standing, 29" high - sitting, 32" high - wheelchair. Optional heights of 27" and 25" may be specified at no additional up-charge.									
ELECTRICAL ACCESSORIES: Each table shall receive 3" diameter black plastic grommets and a black steel J-channel for wire management. The J-channel will be mounted to the underside of the top by means of wood screws.									

	MODEL NUMBER	PRODUCT	W	D	H	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
	EL-R36	Round Reading Tables	36"	36"	29"	90 Lbs.	8 Cu Ft	\$ 2,295	TABLE TOP: Table tops shall be constructed of 1 ¹ / ₄ " thick 3 ply particleboard core. Top surface to be laminated with a .050" thick high pressure plastic laminate sheet. Bottom surface to be laminated with a backing sheet not less than .020" thick. Surrounding edges shall receive a 1 ¹ / ₄ " x 1 ¹ / ₄ " solid external hardwood edge. Edges shall be applied to top after the top and bottom laminate sheets have been applied. Two working edges on rectangular tables and square tables shall receive a 5" wide plastic laminate strip. Circular tables do not receive the laminate strip. Tops shall receive a 1 ¹ / ₃₂ " v-groove detail where Laminate and solid meet.
	EL-R42		42"	42"	29"	90 Lbs.	8 Cu Ft	\$ 2,360	
	EL-R48		48"	48"	29"	100 Lbs.	10 Cu Ft	\$ 2,425	
	EL-R60		60"	60"	29"	155 Lbs.	10 Cu Ft	\$ 2,790	
	EL-4242	Square ReadingTables	42"	42"	29"	170 Lbs.	8 Cu Ft	\$ 2,310	TABLE TOP SUPPORTS: All tables 60" and longer shall be fitted with a v-shaped, 14 gauge steel keel. The keel shall be mounted to the underside of the top by means of wood screws. All tables 48" wide and 60" long and longer shall be fitted with two parallel steel keels.
	EL-4848		48"	48"	29"	230 Lbs.	10 Cu Ft	\$ 2,370	
	EL-6036	60" Wide Rectangle Reading Tables	60"	36"	29"	200 Lbs.	10 Cu Ft	\$ 2,455	LEG ASSEMBLY: Legs are 2 ³ / ₈ " x 2 ³ / ₈ " glued up solid stock. The two inside edges are tapered down to 1 ¹ / ₂ " x 1 ¹ / ₂ ". The leg is attached to a metal plate by means of two threaded machine bolts fastened to a barrel nut embedded in the leg. Two steel decorative angle bars are attached to the upper outside corners of the leg spaced 5" apart. LEG PLATE: Corner leg plates shall be 5" x 5" x 1 ¹ / ₄ " powder epoxy coated steel plate. Plate and leg assembly shall be mounted to underside of table top by means of threaded inserts embedded in the underside of the top. Inserts are capable of receiving heavy duty Machine bolts. The two inside corners of the plate shall have a fin angled design incorporating support to the leg. GLIDES: Each leg will be fitted with a threaded T-nut to accept a 1 ⁵ / ₈ " Diameter cushioned glide with a 1 ¹ / ₂ " x 3 ³ / ₈ " threaded stem. WORK SURFACE HEIGHT: Standard work surface height is 29" h. Optional heights of 32", wheelchair accessible, 27" and 25" may be specified at no additional charge.
	EL-6048		60"	48"	29"	270 Lbs.	13 Cu Ft	\$ 2,600	
	EL-7236	72" Wide Rectangle Reading Tables	72"	36"	29"	230 Lbs.	12 Cu Ft	\$ 2,520	
	EL-7248		72"	48"	29"	290 Lbs.	15 Cu Ft	\$ 2,675	
	EL-8436	84" Wide Rectangle Reading Tables	84"	36"	29"	290 Lbs.	13 Cu Ft	\$ 2,585	
	EL-8448		84"	48"	29"	290 Lbs.	18 Cu Ft	\$ 2,755	
	EL-9636	96" Wide Rectangle Reading Tables	96"	36"	29"	290 Lbs.	15 Cu Ft	\$ 2,645	
	EL-9648		96"	48"	29"	340 Lbs.	20 Cu Ft	\$ 2,830	