






























	MODEL NUMBER	PRODUCT	WIDTH	DEPTH	HEIGHT	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
	FL-R36-KN-2SQ	ROUND Tables, Knife Edge:	36"	36"	29"	____ Lbs.	____ Cu Ft	\$ 1,765	Constructed of 1-1/8" thick 3-ply particleboard core, with 0.050" thick high pressure plastic laminate sheet on top surface. Bottom surface laminated with a 0.20" thick backing sheet. 
	FL-R42-KN-2SQ		42"	42"	29"	____ Lbs.	____ Cu Ft	\$ 1,960	
	FL-R48-KN-2SQ		48"	48"	29"	____ Lbs.	____ Cu Ft	\$ 2,080	
	FL-R54-KN-2SQ		54"	54"	29"	____ Lbs.	____ Cu Ft	\$ 2,475	
	FL-R60-KN-2SQ		60"	60"	29"	____ Lbs.	____ Cu Ft	\$ 2,775	
	FL-3636-KN-2SQ	SQUARE Tables, Knife Edge:	36"	36"	29"	____ Lbs.	____ Cu Ft	\$ 1,765	Consists of two sets of steel legs and a top horizontal stretcher, constructed of 2" x 2" tubular 16 gauge steel. All metal is expoxy powder coated. Leveler: Legs are fitted with a threaded base to accept a 1/4" thick x 2"x2" square metal adjustable glide.
	FL-4242-KN-2SQ		42"	42"	29"	____ Lbs.	____ Cu Ft	\$ 1,875	
	FL-4848-KN-2SQ		48"	48"	29"	____ Lbs.	____ Cu Ft	\$ 1,995	
	FL-3036-KN-2SQ	RECTANGLE Tables, Knife Edge:	36"	30"	29"	____ Lbs.	____ Cu Ft	\$ 1,690	 17-3/4" I.D. for 36" Diameter 22" I.D. for 42" Diameter 26-1/4" I.D. for 48" Diameter Clean with a non abrasive cleanser. Do not use powdered cleaning solutions as they may scratch the surface.
	FL-3042-KN-2SQ		42"	30"	29"	____ Lbs.	____ Cu Ft	\$ 1,760	
	FL-3048-KN-2SQ		48"	30"	29"	____ Lbs.	____ Cu Ft	\$ 1,815	
	FL-3054-KN-2SQ		54"	30"	29"	____ Lbs.	____ Cu Ft	\$ 1,865	
	FL-3060-KN-2SQ		60"	30"	29"	____ Lbs.	____ Cu Ft	\$ 1,915	
	FL-3072-KN-2SQ		72"	30"	29"	____ Lbs.	____ Cu Ft	\$ 2,015	
	FL-3642-KN-2SQ		42"	36"	29"	____ Lbs.	____ Cu Ft	\$ 1,820	
	FL-3648-KN-2SQ		48"	36"	29"	____ Lbs.	____ Cu Ft	\$ 1,885	
	FL-3654-KN-2SQ		54"	36"	29"	____ Lbs.	____ Cu Ft	\$ 1,925	
	FL-3660-KN-2SQ		60"	36"	29"	____ Lbs.	____ Cu Ft	\$ 1,980	
	FL-3672-KN-2SQ		72"	36"	29"	____ Lbs.	____ Cu Ft	\$ 2,085	

	MODEL NUMBER	PRODUCT	WIDTH	DEPTH	HEIGHT	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
	FL-CS-3630-KN-2SQ	One Place	36"	30"	29"	_____ Lbs.	_____ Cu Ft	\$ 2,405	COMPUTER STATIONS, Knife Edge: Constructed of 1-1/8" thick 3-ply particleboard core, with 0.050" thick high pressure plastic laminate sheet on top surface. Bottom surface laminated with a 0.20" thick backing sheet.
									
									Knife Edge is 2-1/4" wide x 1-3/4" high solid wood, with a 45 miter chamfer with 1/8" radius corners.
									Consists of two sets of steel legs and a top horizontal stretcher, constructed of 2" x 2" tubular 16 gauge steel. All metal is epoxy powder coated.
	FL-CS-D-7230-KN-2SQ	Two Place	72"	30"	29"	_____ Lbs.	_____ Cu Ft	\$ 3,095	Leveler: Legs are fitted with a threaded base to accept a 1/4" thick x 2"x2" square metal adjustable glide.
	FL-CS-2D-3660-KN-2SQ	Two Place, (One Place Back to Back)	36"	60"	29"	_____ Lbs.	_____ Cu Ft	\$ 2,895	
	FL-CS-4D-7260-KN-2SQ	Four Place, (Two Place Back to Back)	72"	60"	29"	_____ Lbs.	_____ Cu Ft	\$ 3,835	Clean with a non abrasive cleanser. Do not use powdered cleaning solutions as they may scratch the surface.
									NOTE: For all Fluid Workstations the list price includes the Acrylic Surround Screen(s), Grommet(s), and J-Channel Wire Management.

	MODEL NUMBER	PRODUCT	WIDTH	DEPTH	HEIGHT	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
	S-FA-S	Frosted Acrylic Screen - Small	20"		8"	2.5 Lbs.	0.5 Cu Ft	\$ 265	
	S-FA-L	Frosted Acrylic Screen - Large	32"		8"	2.5 Lbs.	0.5 Cu Ft	\$ 280	
	S-FAS	Frosted Acrylic Screen Surround	32"	13	8"	9.5 Lbs.	0.5 Cu Ft	\$ 545	
	S-WS	Wood Screen Surround	32"	7	8"	8 Lbs. 8 Lbs.	0.5 Cu Ft 0.5 Cu Ft	\$ 270	
	S-SWM-S	Wood Frame Perforated Metal Screen Small	20"		8"			\$ 500	
	S-SWM-L	Wood Frame Perforated Metal Screen Large	32"		16"			\$ 745	
	S-SWW-S	Wood Screen, Metal Posts Small	20"		8"			\$ 330	
	S-SWW-L	Wood Screen, Metal Posts Large	32"		16"			\$ 495	
	S-SWA	Wood Frame, Metal Posts, Frosted Acrylic Screen	24"		16"			\$ 745	

	MODEL NUMBER	PRODUCT	WIDTH	DEPTH	HEIGHT	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
	PD-BL	Pencil Drawer	20 ⁷ / ₈ "	18 ¹ / ₂ "	1 ⁷ / ₈ "	___ Lbs.	___ Cu Ft	\$ 140	Pencil & paper drawer. Includes roller slides and frame for under-desk mounting. Black finish.
	CD-250-PK	Pullout Keyboard	24"	11"		___ Lbs.	___ Cu Ft	\$ 510	
	CD-250-AK	Articulating Keyboard and Mouse	21"	10"		___ Lbs.	___ Cu Ft	\$ 510	
	PW-G2D	Plastic Grommet 2"	2"	2"	³ / ₄ "	0.1 Lbs.	___ Cu Ft	\$ 85	
	PW-G3D	Plastic Grommet 3"	3"	3"	³ / ₄ "			\$ 85	
	P-TC-V	Vertical Flex Wire Leg	3"	2"	32 ¹ / ₂ "	___ Lbs.	___ Cu Ft	\$ 165	32 ¹ / ₂ " Silver Plastic. Separates wire in different channels for easier maintenance. Kit includes: 1 top bracket, 15 spine wheels, 2 fixing clips for horizontal applications and 1 weighted base. Also comes in Black.
	P-TC	Table Connector	3"	2"		___ Lbs.	___ Cu Ft	\$ 40	
	PW-OWMT-30	Wire Manager	30"	2"		___ Lbs.	___ Cu Ft	\$ 85	

	MODEL NUMBER	PRODUCT	WIDTH	DEPTH	HEIGHT	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
	PW-100-F	Flip-Up Power - 2 outlet, 2 data	9"		5 1/2"	___ Lbs.	___ Cu Ft	\$ 625	Black Metal
	PW-100-J	Jr. Flip-Up Power - 2 outlet, 2 data	5 3/4"		5 1/2"	___ Lbs.	___ Cu Ft	\$ 505	Black Metal
	DTP-BL	Desktop Power and Data	7"		3"	___ Lbs.	___ Cu Ft	\$ 230	Black Plastic
	P-PS-B	Power Sphere - 4 outlets - Black	3"		3"	___ Lbs.	___ Cu Ft	\$ 275	Black Plastic
	P-PDS-B	Power Sphere - 2 outlets, 2 data - Black	3"		3"	___ Lbs.	___ Cu Ft	\$ 215	
	P-PS-T	Power Sphere - 4 outlets - Translucent	3"		3"	___ Lbs.	___ Cu Ft	\$ 275	Translucent Plastic
	P-PDS-T	Power Sphere - 2 outlets, 2 data - Translucent	3"		3"	___ Lbs.	___ Cu Ft	\$ 215	
	PW-SPC-6	6 Outlet Power Bar	11"		2"	___ Lbs.	___ Cu Ft	\$ 125	White Plastic - 15 amp 120V


WOODS & FINISHES:

Natural Maple
Standard



Natural Clear – M-NA

Maple Finishes
The following stains are available, add 10% to list



Honey Oak – M-HO




Castle Oak – M-CO



Richmond Cherry – M-RC




Mahogany – M-MA




Victorian Cherry – M-VI



Java – M-JA



Wenge – M-WE




English Oak – M-EN

Natural Red Oak
Standard



Natural Clear – O-NA

Red Oak Finishes
The following stains are available, add 10% to list



Castle Oak – O-CO



Honey Oak – O-HO




English Oak – O-EN



Victorian Cherry – O-VI



Mahogany – O-MA



Richmond Cherry – O-RC




Java – O-JA




Wenge – O-WE

Natural Cherry
Add 20% to list



Natural Clear – C-NA

Cherry Finishes
The following stains are available, add 30% to list



Honey Oak – C-HO



Richmond Cherry – C-RC

Natural Walnut
Add 20% to list



Natural Clear – W-NA


Walnut Finishes
The following stain is available, add 30% to list



Java – W-JA

LAMINATES:

Melamine Laminate Options



Hardrock Maple – L303



Fidlar's Maple – L363




Cognac Cherry – L448




Cherry Blossom – L449



Almond Cherry – L457




Samba Cherry – L460



Lambada Cherry – L461



Shiraz Cherry – L472



Tuxedo – 477



Hot Cinnamon – L480



Caramel Maple – L490




Antigua – L498



Borneo – L500



Ginger Snap Fruitwood – L518



Very Chic – L666

METAL THERMAL PAINT COLOURS:




Sparkle Silver – S11



Beige – H23



Antique White – W11



White – PS-111-W374



Ruby – R7



Navy – B17




Blue – B11




Teal – HG266




Green – G58



Charcoal – A230



Grey – A16



Black – N49



Black Sandtex – N31
Textured Finish

HARDWOODS: All hardwood materials used in the manufacturing of P2 products shall be Northern grown hardwoods. Hardwoods will be air and kiln dried to a moisture content of 5-7%. All hardwoods shall be of grade “A” material, free of material stains, imperfections, conformity of grain, texture and color. Hardwood species shall be Northern grown Red Oak, Clear White Northern Maple and Birch. American Cherry and Honduras Mahogany and Walnut are available. Please inquire for pricing.

VENEER: Exposed face veneers shall be not less than 1/28" thick plain sliced veneers. Veneers are to be selected for conformity of grain direction and color. Veneers are to be stitched tightly in a book match, slip match or plain sliced configuration. Unexposed veneers are to be of hardwood but not selected for color, or grain quality. Veneers are not to be lap joined or reveal any tape or glue lines.

PARTICLE BOARD CORE: The particleboard shall be formed of wood chips, bonded with a water resistance adhesive. The particleboard material is to be of a high density 45 lbs/cu. ft. having a minimum average modules of rupture of 2400 psi and a minimum average modules of elasticity of 4,000,000 psi.

VENEER CORE: Veneer core is to be constructed with odd numbers of plies. Each ply is to be laminated in pairs and cross banded in opposite directions with grain direction at a 90 degree angle to the grain of the center core. All plies are to be free from knots, wrinkles, laps or other natural or manufacturing defects.

HIGH PRESSURE LAMINATE: Work surface laminate shall be .050" thick and used with balancing backer sheet of no less than .028" thick. Laminate shall conform to standards set by the National Electrical Manufactures' Association (NEMA).

FINISHING PROCEDURES: All materials shall be inspected and treated with a final sanding and polishing operation before any staining and final finishing can be performed. All machine and mill marks are to be removed. Once the polishing and sanding has been performed, the furniture will then undergo the following stain and finishing procedures:

- Step 1: A base stain will be uniformly applied, wiped and then allowed to dry under factory controlled conditions.
- Step 2: A uniform coat of sealer will be applied and allowed to dry.
- Step 3: Sealer will be lightly sanded using 240 grit silicon paper.
- Step 4: A catalytic lacquer of 34-45 degree sheen is evenly applied and allowed to dry under factory controlled conditions.

METAL FINISHING PROCEDURES: All metal components are thoroughly cleaned and coated electrostatically with an epoxy powder coat paint finish. The metal components are then oven baked and cured for a lasting finish.

