



119



120




231



234




262



331



333



377




380




443



496



532




534



571



625




629



236



378



533



651

MIRAGE FABRIC SPECIFICATION:

Abrasion Test: Martindale UNI EN ISO 12947 2000. 100,000 turns +/- 20%

Cleaning Instruction: Water/Solvent Based Cleaner. Do not bleach

Colors Available: 20 colors available.

Construction: Crepe

Content: 100% Polyester

Description: Woven Solid

Fire Retardancy: I: Class 1, F: M1, D: B1 DIN4102. GB: BS 7176 Medium Hazard. Q1 (OENORM 3800 Part 1). B1 (OENORM B3825

Lightfastness: (Xenotest) UNI EN ISO 105 B02 5 +/- 1

Weight: 490 grams per linear meter



Light Beige 404



Beige 401



Orange Black 406



Orange White 300



Red 302



Red Black 306



Light Brown 403



Mid Brown 402



Pink 003




Mauve 001




Burgandy 002



Light Grey 600




Light Blue 701



Navy 702



Bright Green 802



Grey Green 801




Orange 303



Deep Brown 405



Dark Grey 200



Black 201

NORD WOOL FABRIC SPECIFICATION:

Abrasion Test: > 30,000 cycles

Cleaning Instruction: Water/Solvent Based Cleaner. Do not bleach

Colors Available: 20 colors available.

Content: 70% Wool (WO) 25% Polyamide/Nylon (PA) 5% Other Fibres (AF)

Description: Solid

Fire Retardancy: EN 1021-1 Cigaret Test: Pass; EN 1021-2 Match Flame Test: Pass

Color Fasteness to Artificial Light: 5

Color Fasteness to Crocking: Dry 4/5. Wet 4/5

Resistance to Pilling: 4/5

Weight: 345 grams per square meter