








| | MODEL NUMBER | PRODUCT | W | D | H | WEIGHT | VOLUME | LIST PRICE | DESCRIPTION |
|--|-----------------|-----------------|-----|-----|-----|----------|----------|---------------|---|
|  | PT-NP | Newspaper Table | 36" | 26" | 38" | 190 Lbs. | 25 Cu Ft | \$ 4,375 | <p>TABLE RACK: Open frame construction using 1" solid hardwood, all edges eased. Newspaper stick holder is fitted on either side of rack to accommodate newspaper sticks. Each holder will have ten 1 1/4" wide cut-outs to allow for 10 sticks. Table rack mounted to panels by means of wood cleats and screws.</p> <p>End panels shall be constructed 2 1/2" thick built-up high density particle core, with premium grade "A" face veneers. The front panel face shall be designed using rift-cut veneers 2" wide running horizontally and vertically around the perimeter of the panel meeting at mitered corners. Panels are framed on four sides with 1/8" thick x 2 1/2" wide solid hardwood, having the top and bottom members overlapping the vertical edges. The center of the panel will then be routed to insert a 16 1/4" long x 3/16" thick x 1/8" deep solid black inlay. The base shall be constructed in a podium fashion with 1/4" thick x 4" high solid hardwood faces mitered on four sides of the panel. A 2" thick x 6" high solid hardwood keel shall be fitted between the panels by means of metal key-hole inserts and fasteners.</p> <p>GLIDES: The underside of each panel will be routed and countersunk to accept two leveling glides.</p> <p>Newspaper Sticks are solid maple and divided into six segments, each complete with a black rubber retainer ring.</p> <p>NOTE: Table rack comes complete with ten newspaper sticks.</p> |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |




| | MODEL NUMBER | PRODUCT | W | D | H | WEIGHT | VOLUME | LIST PRICE | DESCRIPTION |
|--|-----------------|-------------|----------------------------------|----------------------------------|----------------------------------|----------|----------|---------------|---|
|  | PT-AS | Atlas Stand | 32 ¹ / ₂ " | 29 ¹ / ₂ " | 44 ¹ / ₂ " | 270 Lbs. | 33 Cu Ft | \$ 4,660 | <p>CABINET CONSTRUCTION: A ³/₄" thick particleboard core back complete with grade "A" veneer faces shall be attached to the panels by means of hidden key-hole fasteners. Unit will come complete with five pull-out shelves operating on blum slides and a fixed bottom.</p> <p>TOP: Sloped top assembly shall be constructed from ³/₄" thick high density particleboard core, assembled by means of tongue and groove. All surfaces of top to be laminated with a .050" thick laminate. Top will be fitted with a book support rail ⁵/₈" thick x ⁵/₈" deep.</p> <p>End panels shall be constructed 2¹/₂" thick built-up high density particle core, with premium grade "A" face veneers. The front panel face shall be designed using rift-cut veneers 2" wide running horizontally and vertically around the perimeter of the panel meeting at mitered corners. Panels are framed on four sides with ¹/₈" thick x 2¹/₂" wide solid hardwood, having the top and bottom members overlapping the vertical edges. The center of the panel is routed to insert a 29" long x ³/₁₆" thick x ¹/₈" deep solid black inlay. The base shall be constructed in a podium fashion with ¹/₄" thick x 4" high solid hardwood faces mitered on four sides of the panel.</p> <p>GLIDES: The underside of each panel will be routed and countersunk to accept two leveling glides.</p> <p>Shelves and bottom constructed from ³/₄" thick plywood with grade "A" veneer on both faces, front edge of shelf and bottom banded with a ³/₄" thick x 1³/₄" high solid retainer lip and drop edge.</p> |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |




| | MODEL NUMBER | PRODUCT | W | D | H | WEIGHT | VOLUME | LIST PRICE | DESCRIPTION |
|--|-----------------|------------------|----------------------------------|----------------------------------|----------------------------------|----------|----------|---------------|--|
|  | PT-DC | Dictionary Stand | 28 ¹ / ₄ " | 16 ³ / ₄ " | 44 ¹ / ₂ " | 190 Lbs. | 16 Cu Ft | \$ 3,375 | <p>CABINET CONSTRUCTION: A ³/₄" thick particleboard core back complete with grade "A" veneer faces shall be attached to the panels by means of hidden key-hole fasteners.</p> <p>TOP: Sloped top assembly shall be constructed from ³/₄" thick high density particleboard core, assembled by means of tongue and groove. All surfaces of top to be laminated with a .050" thick laminate. Top will be fitted with a book support rail ⁵/₈" thick x ⁵/₈" deep.</p> <p>End panels shall be constructed 2¹/₂" thick built-up high density particle core, with premium grade "A" face veneers. The front panel face shall be designed using rift-cut veneers 2" wide running horizontally and vertically around the perimeter of the panel meeting at mitered corners. Panels are framed on four sides with ¹/₈" thick x 2¹/₂" wide solid hardwood, having the top and bottom members overlapping the vertical edges. The center of the panel will then be routed to insert a 30" long x ³/₁₆" thick x ¹/₈" deep solid black inlay. The base shall be constructed in a podium fashion with ¹/₄" thick x 4" high solid hardwood faces mitered on four sides of the panel.</p> <p>GLIDES: The underside of each panel will be routed and countersunk to accept two leveling glides.</p> <p>Unit will come complete with one shelf and a fixed bottom, constructed from ³/₄" thick plywood with grade "A" veneer on both faces, front edge of shelf banded with a ¹/₄" thick solid hardwood. Shelf will be adjustable on 1¹/₄" increments. The fixed bottom shelf will have a ³/₄" x 1³/₄" drop edge mounted to the front edge.</p> |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |




| | MODEL NUMBER | PRODUCT | W | D | H | WEIGHT | VOLUME | LIST PRICE | DESCRIPTION |
|--|-----------------|--|----------------------------------|----------------------------------|-----|----------|----------|---------------|---|
|  | PT-DP | Display Table | 30 ¹ / ₂ " | 62 ¹ / ₂ " | 39" | 255 Lbs. | 23 Cu Ft | \$ 8,690 | CASE CONSTRUCTION: Wood framing constructed from 1 ¹ / ₂ " x 1 ¹ / ₂ " solid. Framing to be routed to receive 1/4" thick glass on all four sides. Wood framing shall incorporate glass by means of tongue and groove assembly. All wood edges to be slightly radiused. The back side of the case is equipped with sliding glass doors complete with lock. Case will be fastened to top by means of wood screws. |
| | PT-DP-FB | Display Table Fabric Covered Bottom | 30 ¹ / ₂ " | 62 ¹ / ₂ " | 39" | 255 Lbs. | 23 Cu Ft | \$ 9,355 | <p>Display top shall be constructed of 1¹/₄" thick 3 ply particleboard core. Top surface to be laminated with a .050" thick high pressure laminate sheet, bottom surface laminated with a backing sheet not less than .020" thick. The four edges will have a 1/4" thick solid internal band, edges will be banded before the laminate and backer sheets have been applied. All edges shall be eased.</p> <p>TOP SUPPORT: A 2" thick x 6" high solid hardwood keel shall be fitted between the panels and the underside of the top by means of metal key-hole inserts, fasteners and wood screws.</p> <p>PODIUM BASE PANEL: Base panels shall be constructed 3" thick built-up high density particle core, with premium grade "A" face veneers. The panels shall be designed with a 4¹/₄" wide x 1/2" deep indentation separating two raised panel faces. The center indentation shall receive a 3/16" thick x 1/8" deep solid black inlay, the inlay will begin and end 2" from the top and bottom. The front panel of each face shall be designed using rift-cut veneers 2" wide running horizontally and vertically around the perimeter of the panel meeting at mitered corners. Panels are framed on four sides with 1/8" thick x 3" wide solid hardwood, having the top and bottom members overlapping the vertical edges. The base shall be constructed in a podium fashion with 1/4" thick x 4" high solid hardwood faces mitered on four sides of the panel and throughout the indentation.</p> <p>GLIDES: The underside of each panel will be routed and countersunk to accept two leveling glides.</p> <p>OPTION: Display table with fabric covered bottom (PR-156-FB)</p> |




| | MODEL NUMBER | PRODUCT | W | D | H | WEIGHT | VOLUME | LIST PRICE | DESCRIPTION |
|--|-----------------|------------|----------------------------------|----------------------------------|----------------------------------|----------|----------|---------------|---|
|  | PT-AV | AV Browser | 52 ¹ / ₄ " | 23 ¹ / ₂ " | 42 ¹ / ₂ " | 260 Lbs. | 37 Cu Ft | \$ 4,370 | <p>MULTIMEDIA DISPLAY BIN: Constructed from ³/₄" thick 3 ply particleboard core with grade "A" face veneer. Storage bin is divided into 7 compartments each 6¹/₄" wide complete with six removable black ¹/₄" thick masonite dividers. Bottom of bin will be lined with black ribbed rubber. Bin capacity approximately 290 compact discs. Unit may also accommodate tapes.</p> <p>End panels shall be constructed 2¹/₂" thick built-up high density particle core, with premium grade "A" face veneers. The front panel face shall be designed using rift-cut veneers 2" wide running horizontally and vertically around the perimeter of the panel meeting at mitered corners. Panels are framed on four sides with ¹/₈" thick x 2¹/₂" wide solid hardwood, having the top and bottom members overlapping the vertical edges. The center of the panel will then be routed to insert a 28" long x ³/₁₆" thick x ¹/₈" deep solid black inlay. The base shall be constructed in a podium fashion with ¹/₄" thick x 4" high solid hardwood faces mitered on four sides of the panel. A 2" thick x 6" high solid hardwood keel shall be fitted between the panels by means of metal key-hole inserts and fasteners.</p> <p>GLIDES: The underside of each panel will be routed and countersunk to accept two leveling glides.</p> |
| | | | | | | | | | |


| | MODEL NUMBER | PRODUCT | W | D | H | WEIGHT | VOLUME | LIST PRICE | DESCRIPTION |
|--|-----------------|--|-----|-----|----------------------------------|----------|----------|---------------|--|
|  | PT-IT-DS-4P | 4 Person Index Table Double Sided Double Tier | 60" | 48" | 52 ³ / ₄ " | 440 Lbs. | 64 Cu Ft | \$ 7,655 | <p>SUPERSTRUCTURE: Side panels, mid panels, shelves and back shall be constructed from ³/₄" thick veneer plywood. All edges and corners shall be eased. The top of the side and back panels shall be banded with a ³/₄" thick x 2" high solid, the front and back vertical edges shall be banded with ¹/₈" thick solid hardwood. Side Panels shall be tapered down from a top dimension of 17" wide to 20" wide at the bottom. Rack dimensions shall be 23³/₄" high x 20" deep. The back panel shall be 23⁵/₈" high. The rack shall be inset 1¹/₂" from the side edges and centered on the work surface. The shelves shall be 8¹/₄" deep with premium grade "A" face veneer, the front edge banded with a ¹/₄" solid external hardwood edge. The shelf shall be installed 13" above the work surface. The outside faces of each side panel shall be accentuated with a ³/₁₆" thick x ¹/₈" deep solid black inlay. The inlay will begin 4" below the top edge of the panel and 2" up from the bottom of the panel. The superstructure shall be assembled by means concealed metal key-hole fasteners. Mounted to the work surface by means of wood screws passing through the underside of the top and into the rack.</p> <p> veneer TOP (OPTION): Top shall constitute the same construction as above only that the work surface will be veneered and finished with a polyurethane finish. The work surface shall be accentuated with a black reveal. A ³/₁₆" black reveal shall be inlayed 7" from the leading edge on either side of the work surface and run horizontally across the table and down the side edges.</p> <p>TOP SUPPORT: A 2" thick x 6" high solid hardwood keel shall be fitted between the panel bases and the underside of the sub-top by means of metal key-hole inserts, fasteners and wood screws.</p> <p>PODIUM END PANEL: Base panels shall be constructed 3" thick built-up high density particle core, with premium grade "A" face veneers. The panels shall be designed with a 4¹/₄" wide x ¹/₂" deep indentation separating two raised panel faces. The center indentation shall receive a ³/₁₆" thick x ¹/₈" deep solid black inlay, the inlay will begin and end 2" from the top and bottom. The front panel of each face shall be designed using rift-cut veneers 2" wide running horizontally and vertically around the perimeter of the panel meeting at mitered corners, thus giving a raised panel effect. Panels are framed on four sides with a ¹/₈" thick x 3" wide solid hardwood, having the top and bottom members overlapping the vertical edges. The base shall be constructed in a podium fashion with ¹/₄" thick x 4" high solid hardwood faces mitered on four sides of the panel and throughout the indentation."</p> <p>GLIDES: The underside of each panel will be routed and countersunk to accept two leveling glides.</p> |
|  | PT-IT-DS-6P | 6 Person Index Table Double Sided Double Tier | 90" | 48" | 52 ³ / ₄ " | 470 Lbs. | 96 Cu Ft | \$ 8,430 | |

| | MODEL NUMBER | PRODUCT | W | D | H | WEIGHT | VOLUME | LIST PRICE | DESCRIPTION |
|---|-----------------|---------------------------|----------------------------------|----------------------------------|-----|----------|----------|---------------|---|
|  | PT-MC-SS | Single Modular Carrel | 35 ³ / ₄ " | 26 ¹ / ₂ " | 48" | 140 Lbs. | 16 Cu Ft | \$ 4,765 | <p>SUPERSTRUCTURE: Side panels, mid panels, shelves and back shall be constructed from ³/₄" thick veneer plywood. All edges and corners shall be eased. The top of the side and back panels shall be banded with a ³/₄" thick x 2" high solid, the front and back vertical edges shall be banded with ¹/₈" thick solid hardwood. Single face study carrel panels shall be tapered down from a top dimension of 15⁷/₈" wide to 17³/₈" wide at the bottom. Double face carrel panels shall be tapered down from a top dimension of 27" wide to 30" wide at the bottom. Single face rack shall be 19" high x 17³/₈" deep, double face rack shall be 19" high x 30" deep. The back panel for both single and double face units shall be 18⁷/₈" high. The rack on single face units shall be inset 1³/₈" from the back edge and 1¹/₂" from the side edges. The rack on double face units shall be centered on the work surface. The shelf for both single face and double face units shall be 9" deep wit premium grade "A" face veneer, the front edge banded with a ¹/₄" solid external hardwood edge. The shelf shall be installed 15" above the work surface. The outside faces of each side panel shall be accentuated with a ³/₁₆" thick x ¹/₈" deep solid black inlay. The inlay will begin 4" below the top edge of the panel and 2" up from the bottom of the panel. The superstructure shall be assembled by means concealed metal key-hole fasteners. Mounted to the work surface by means of wood screws passing through the underside of the top and into the rack.</p> <p> veneer TOP (OPTION): Top shall constitute the same construction as above only that the work surface will be veneered and finished with a polyurethane finish. The work surface shall be accentuated with a black reveal. A ³/₁₆" black reveal shall be inlayed 7" from the leading edge and run horizontally across the table and down the work surface. Single face units shall receive one reveal inlay and two reveal inlays for double face units.</p> <p>TOP SUPPORT: A 2" thick x 6" high solid hardwood keel shall be fitted between the panel bases and the underside of the sub-top by means of metal key-hole inserts, fasteners and wood screws.</p> <p>PODIUM END PANEL - SINGLE FACE CARREL: Base panels shall be constructed 2¹/₂" thick built-up high density particle core, with premium grade "A" face veneers. The front panel face shall be designed using rift-cut veneers 2" wide running horizontally and vertically around the perimeter of the panel meeting at mitered corners, thus giving a raised panel effect. Panels are framed on four sides with ¹/₈" thick x 2¹/₂" wide solid hardwood, having the top and bottom members overlapping the vertical edges. The center of the panel will then be routed to insert a 14¹/₄" long x ³/₁₆" thick x ¹/₈" deep solid black inlay. The base shall be constructed in a podium</p> |
|  | PT-MC-DS | Double Modular Carrel | 35 ³ / ₄ " | 48" | 48" | 210 Lbs. | 32 Cu Ft | \$ 7,495 | |
|  | PT-MC-Q | Four Place Modular Carrel | 70 ¹ / ₂ " | 48" | 48" | 310 Lbs. | 62 Cu Ft | \$ 8,110 | |

| | MODEL NUMBER | PRODUCT | W | D | H | WEIGHT | VOLUME | LIST PRICE | DESCRIPTION |
|--|-----------------|-----------------------|-----|-----|-----|----------|----------|---------------|--|
|  | | 1 Person PAC Tables: | | | | | | | <p>SUPERSTRUCTURE: Side panels, and back shall be constructed from 3/4" thick solid hardwood. All edges and corners shall be eased. The side panels shall be tapered down from a top dimension of 7" wide to 8" wide at the bottom. Single face rack shall be 8" high x 8" deep, double face rack shall be constructed from 3/4" thick veneer plywood 8" high x 15" deep. The back panel for both single and double face units shall be 77/8" high. The rack on single face units shall be inset 13/8" from the back edge and 11/2" from the side edges. The rack on double face units shall be centered on the work surface.</p> <p> veneer TOP (OPTION): Top shall constitute the same construction as above only that the work surface will be veneered and finished with a polyurethane finish. The work surface shall be accentuated with a black reveal. A 3/16" black reveal shall be inlayed 7" from the leading edge and run horizontally across the table and down the work surface. Single face units shall receive one reveal inlay and two reveal inlays for double face units.</p> <p>TOP SUPPORT: A 2" thick x 6" high solid hardwood keel shall be fitted between the panel bases and the underside of the sub-top by means of metal key-hole inserts, fasteners and wood screws.</p> <p>PODIUM END PANEL - SINGLE FACE PAC: Base panels shall be constructed 21/2" thick built-up high density particle core, with premium grade "A" face veneers. The front panel face shall be designed using rift-cut veneers 2" wide running horizontally and vertically around the perimeter of the panel meeting at mitered corners, thus giving a raised panel effect. Panels are framed on four sides with 1/8" thick x 21/2" wide solid hardwood, having the top and bottom members overlapping the vertical edges. The center of the panel will then be routed to insert a 141/4" long x 3/16" thick x 1/8" deep solid black inlay. The base shall be constructed in a podium fashion with 1/4" thick x 4" high solid hardwood faces mitered on four sides of the panel. A 2" thick x 6" high solid hardwood keel shall be fitted between the panels by means of metal key-hole inserts and fasteners.</p> <p>PODIUM END PANEL - DOUBLE FACE PAC: Base panels shall be constructed 3" thick built-up high density particle core, with premium grade "A" face veneers. The panels shall be designed with a 41/4" wide x 1/2" deep indentation separating two raised panel faces. The center indentation shall receive a 3/16" thick x 1/8" deep solid black inlay, the inlay will begin and end 2" from the top and bottom. The front panel of each face shall be designed using rift-cut veneers 2" wide running horizontally and vertically around the perimeter of the panel meeting at mitered corners, thus giving a raised panel effect. Panels are framed on four sides with a 1/8" thick x 3" wide solid hardwood, having the top and bottom members overlapping</p> |
| | PT-PAC-1-29 | Sitting Height | 36" | 36" | 37" | 135 Lbs. | 13 Cu Ft | \$ 4,710 | |
| | PT-PAC-1-32 | Wheelchair Accessible | 36" | 36" | 40" | 135 Lbs. | 16 Cu Ft | \$ 4,730 | |
| | PT-PAC-1-39 | Standing Height | 36" | 36" | 47" | 140 Lbs. | 23 Cu Ft | \$ 4,790 | |
|  | | 2 Person PAC Tables: | | | | | | | |
| | PT-PAC-2-29 | Sitting Height | 72" | 36" | 37" | 205 Lbs. | 27 Cu Ft | \$ 5,070 | |
| | PT-PAC-2-32 | Wheelchair Accessible | 72" | 36" | 40" | 205 Lbs. | 33 Cu Ft | \$ 5,095 | |
| | PT-PAC-2-39 | Standing Height | 72" | 36" | 47" | 210 Lbs. | 46 Cu Ft | \$ 5,150 | |
|  | | 3 Person PAC Tables: | | | | | | | |
| | PT-PAC-3-29 | Sitting Height | 90" | 36" | 37" | 260 Lbs. | 34 Cu Ft | \$ 5,480 | |
| | PT-PAC-3-32 | Wheelchair Accessible | 90" | 36" | 40" | 260 Lbs. | 41 Cu Ft | \$ 5,505 | |
| | PT-PAC-3-39 | Standing Height | 90" | 36" | 47" | 270 Lbs. | 58 Cu Ft | \$ 5,560 | |

| | MODEL NUMBER | PRODUCT | W | D | H | WEIGHT | VOLUME | LIST PRICE | DESCRIPTION |
|--|-----------------|--|-----|-----|-----|----------|----------|---------------|---|
|  | | 2 Person (1 Place Back to Back) PAC Tables: | | | | | | | SUPERSTRUCTURE: Side panels, and back shall be constructed from 3/4" thick solid hardwood. All edges and corners shall be eased. The side panels shall be tapered down from a top dimension of 7" wide to 8" wide at the bottom. Single face rack shall be 8" high x 8" deep, double face rack shall be constructed from 3/4" thick veneer plywood 8" high x 15" deep. The back panel for both single and double face units shall be 77/8" high. The rack on single face units shall be inset 13/8" from the back edge and 11/2" from the side edges. The rack on double face units shall be centered on the work surface. |
| | PT-PAC-1D-29 | Sitting Height | 36" | 60" | 37" | 260 Lbs. | 22 Cu Ft | \$ 7,410 | |
| | PT-PAC-1D-32 | Wheelchair Accessible | 36" | 60" | 40" | 260 Lbs. | 27 Cu Ft | \$ 7,450 | |
| | PT-PAC-1D-39 | Standing Height | 36" | 60" | 47" | 270 Lbs. | 38 Cu Ft | \$ 7,555 | |
|  | | 4 Person (2 Place Back to Back) PAC Tables: | | | | | | | VENEER TOP (OPTION): Top shall constitute the same construction as above only that the work surface will be veneered and finished with a polyurethane finish. The work surface shall be accentuated with a black reveal. A 3/16" black reveal shall be inlayed 7" from the leading edge and run horizontally across the table and down the work surface. Single face units shall receive one reveal inlay and two reveal inlays for double face units. TOP SUPPORT: A 2" thick x 6" high solid hardwood keel shall be fitted between the panel bases and the underside of the sub-top by means of metal key-hole inserts, fasteners and wood screws. |
| | PT-PAC-2D-29 | Sitting Height | 72" | 60" | 37" | 400 Lbs. | 45 Cu Ft | \$ 8,045 | |
| | PT-PAC-2D-32 | Wheelchair Accessible | 72" | 60" | 40" | 400 Lbs. | 54 Cu Ft | \$ 8,085 | |
| | PT-PAC-2D-39 | Standing Height | 72" | 60" | 47" | 410 Lbs. | 77 Cu Ft | \$ 8,185 | |
|  | | 6 Person (3 Place Back to Back) PAC Tables: | | | | | | | PODIUM END PANEL - SINGLE FACE PAC: Base panels shall be constructed 21/2" thick built-up high density particle core, with premium grade "A" face veneers. The front panel face shall be designed using rift-cut veneers 2" wide running horizontally and vertically around the perimeter of the panel meeting at mitered corners, thus giving a raised panel effect. Panels are framed on four sides with 1/8" thick x 21/2" wide solid hardwood, having the top and bottom members overlapping the vertical edges. The center of the panel will then be routed to insert a 141/4" long x 3/16" thick x 1/8" deep solid black inlay. The base shall be constructed in a podium fashion with 1/4" thick x 4" high solid hardwood faces mitered on four sides of the panel. A 2" thick x 6" high solid hardwood keel shall be fitted between the panels by means of metal key-hole inserts and fasteners. PODIUM END PANEL - DOUBLE FACE PAC: Base panels shall be constructed 3" thick built-up high density particle core, with premium grade "A" face veneers. The panels shall be designed with a 41/4" wide x 1/2" deep indentation separating two raised panel faces. The center indentation shall receive a 3/16" thick x 1/8" deep solid black inlay, the inlay will begin and end 2" from the top and bottom. The front panel of each face shall be designed using rift-cut veneers 2" wide running horizontally and vertically around the perimeter of the panel meeting at mitered corners, thus giving a raised panel effect. Panels are framed on four sides with a 1/8" thick x 3" wide solid hardwood, having the top and bottom members overlapping |
| | PT-PAC-3D-29 | Sitting Height | 90" | 60" | 37" | 500 Lbs. | 56 Cu Ft | \$ 8,590 | |
| | PT-PAC-3D-32 | Wheelchair Accessible | 90" | 60" | 40" | 500 Lbs. | 68 Cu Ft | \$ 8,630 | |
| | PT-PAC-3D-39 | Standing Height | 90" | 60" | 47" | 520 Lbs. | 96 Cu Ft | \$ 8,730 | |

| | MODEL NUMBER | PRODUCT | W | D | H | WEIGHT | VOLUME | LIST PRICE | DESCRIPTION |
|---|-----------------|-----------------------------------|-----|-----|-----|----------|----------|---------------|--|
|  | PT-R42 | Round Reading Tables | 42" | 42" | 29" | 90 Lbs. | 8 Cu Ft | \$ 2,610 | APRON: A solid apron base 3/4" thick x 33/8" shall be fitted together by means of metal corner brackets. The underside of the base shall be machined to form an arch beginning 5" from either side and arching in upwards towards the center of the base. The base shall be fastened to the underside of the table top by means of metal "L" brackets and wood screws. |
| | PT-R48 | | 48" | 48" | 29" | 100 Lbs. | 10 Cu Ft | \$ 2,735 | |
|  | PT-4242 | Square ReadingTables | 42" | 42" | 29" | 90 Lbs. | 8 Cu Ft | \$ 2,195 | TABLE TOP (SQUARE AND RECTANGULAR): Table tops shall be constructed of 1 1/4" thick 3 ply particleboard core. Top surface to be laminated with a .050" thick high pressure plastic laminate sheet, bottom surface laminated with a backing sheet not less than .020" thick for balanced construction. Plastic laminate will meet or exceed NEMA standards. Table edges shall be 2 1/4" wide x 1 5/8" thick solid hardwood. The edge shall be machined in two parts, 3/4 of the leading edge shall be radiused 3/8" top and bottom, the remaining solid shall be chamfered inward creating a knife edge detail. The edges shall be mitered at four corners. |
| | PT-4848 | | 48" | 48" | 29" | 100 Lbs. | 10 Cu Ft | \$ 2,330 | |
|  | PT-6036 | 60" Wide Rectangle Reading Tables | 60" | 36" | 29" | 170 Lbs. | 10 Cu Ft | \$ 2,680 | TABLE TOP (CIRCULAR): Circular tables shall receive a 2 1/4" wide x 1 1/4" thick solid edge band. The edges shall be fabricated in four section. All edges are eased |
| | PT-6048 | | 60" | 48" | 29" | 230 Lbs. | 13 Cu Ft | \$ 2,840 | |
| | PT-7236 | 72" Wide Rectangle Reading Tables | 72" | 36" | 29" | 200 Lbs. | 12 Cu Ft | \$ 2,810 | TABLE TOP SUPPORTS: All tables 60" and longer shall be fitted with a V-shaped, 14 gauge steel keel. The keel shall be mounted to the underside of the top by means of wood screws. All tables 48" wide and 60" long and longer shall be fitted with two parallel running steel keels. |
| | PT-7248 | | 72" | 48" | 29" | 270 Lbs. | 15 Cu Ft | \$ 2,985 | |
| | PT-8436 | 84" Wide Rectangle Reading Tables | 84" | 36" | 29" | 250 Lbs. | 13 Cu Ft | \$ 2,945 | LEG ASSEMBLY: Legs are 2 3/8" x 2 3/8" glued-up solid stock, all edges eased. Each leg shall receive a 1/8" x 1/8" reveal saw cut 2 1/2" from the bottom of the leg. Each leg will be fitted with a hanger bolt which shall pass between the intersecting rails and through the metal corner bracket. |
| | PT-8448 | | 84" | 48" | 29" | 280 Lbs. | 18 Cu Ft | \$ 3,125 | |
| | PT-9636 | 96" Wide Rectangle Reading Tables | 96" | 36" | 29" | 310 Lbs. | 15 Cu Ft | \$ 3,075 | GLIDES: Each leg will be fitted with a threaded T-nut to accept a 1 1/8" diameter cushioned glide with a 1" x 5/16" threaded stem. |
| | PT-9648 | | 96" | 48" | 29" | 320 Lbs. | 20 Cu Ft | \$ 3,270 | |
| | | | | | | | | | WORKSURFACE HEIGHT: Standard work surface height shall be 29" high. Optional heights of 32" - wheelchair, 27" and 25" may be specified at no additional upcharge. |

| | MODEL NUMBER | PRODUCT | W | D | H | WEIGHT | VOLUME | LIST PRICE | DESCRIPTION |
|--|-----------------|--|-----|-----|-----|----------|----------|---------------|--|
|  | PT-6048-PB | 60" Wide Rectangle Panel Base Reading Table | 60" | 48" | 29" | 250 Lbs. | 21 Cu Ft | \$ 6,045 | <p>PODIUM BASE PANEL: Base panels shall be constructed 3" thick built-up high density particle core, with premium grade "A" face veneers. The panels shall be designed with a 4¹/₄" wide x 1¹/₂" deep indentation separating two raised panel faces. The center indentation shall receive a 3³/₁₆" thick x 1¹/₈" deep solid black inlay, the inlay will begin and end 2" from the top and bottom. The front panel of each face shall be designed using rift-cut veneers 2" wide running horizontally and vertically around the perimeter of the panel meeting at mitered corners, thus giving a raised panel effect. Panels are framed on four sides with 1¹/₈" thick x 3" wide solid hardwood, having the top and bottom members overlapping the vertical edges. The base shall be constructed in a podium fashion with 1¹/₄" thick x 4" high solid hardwood faces mitered on four sides of the panel and throughout the indentation.</p> <p> veneer TOP (OPTION): Work surface shall constitute the same construction as above only that the top will be veneered and finished with a polyurethane finish. The work surface shall be accentuated with a black reveal. A 3³/₁₆" black reveal shall be inlayed 7" from the leading edge and run horizontally across the table and down the top on either side.</p> <p>TOP SUPPORT: A 2" thick x 6" high solid hardwood keel shall be fitted between the panels and the underside of the sub-top by means of metal key-hole inserts, fasteners and wood screws.</p> <p>GLIDES: Each leg will be fitted with a threaded T-nut to accept a 1¹/₈" diameter cushioned glide with a 1" x 5⁵/₁₆" threaded stem.</p> <p>WORK SURFACE: Work surface shall be constructed 2" thick built-up high density particle core. Work surface to be laminated with a .050" thick high pressure laminate sheet, bottom surface laminated with a backing sheet not less than .020" thick. The two long horizontal edges of the work surface shall be banded with a 2" wide x 2" thick solid external edge. The edge shall be machined inward creating a chamfered knife edge detail. The finished edge shall be 3³/₄" thick at the leading edge and 2" thick at the back. The top and bottom of the leading edge shall be radiused 3³/₁₆". The two short vertical edges shall be externally banded with 1¹/₈" thick x 2" high solid hardwood. Edges shall be banded to top after the top and bottom laminate sheets have been applied. The tapered edges of the work surface shall extend 8³/₄" beyond the table bases. A 3³/₄" thick sub-top shall be incorporated into the construction and assembly of the top and the base panels. The sub-top shall be fastened to the top by means of wood screws passing through the sub-top and into the work surface.</p> <p>WORK SURFACE HEIGHT: Standard work surface height shall be 29" high. Optional heights of 32" - wheelchair, 27" and 25" may be specified at no additional upcharge</p> |
| | PT-7248-PB | 72" Wide Rectangle Panel Base Reading Table | 72" | 48" | 29" | 310 Lbs. | 30 Cu Ft | \$ 6,130 | |
| | PT-8448-PB | 84" Wide Rectangle Panel Base Reading Table | 84" | 48" | 29" | 250 Lbs. | 21 Cu Ft | \$ 6,430 | |
| | PT-9648-PB | 96" Wide Rectangle Panel Base Reading Table | 96" | 48" | 29" | 330 Lbs. | 34 Cu Ft | \$ 6,515 | |