








	MODEL NUMBER	PRODUCT	W	D	H	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
	AP-NP	Newspaper Table	39 ¹ / ₂ "	27"	30"	180 Lbs.	21 Cu Ft	\$ 2,710	<p>TABLE RACK: Open frame construction using 1" solid hardwood, all edges eased. Newspaper stick holder is fitted on either side of rack to accommodate newspaper sticks. Each holder will have ten 1¹/₄" wide cut-outs to allow for 10 sticks.</p> <p>Each leg is fitted with a threaded T-nut to accept a 1¹/₈" diameter cushioned glide with a 1" x ⁵/₁₆" threaded stem.</p> <p>Newspaper Sticks are solid maple and divided into six segments, each complete with a black rubber retainer ring. NOTE: Table rack comes complete with ten newspaper sticks.</p>
	AP-AS	Atlas Stand	30 ¹ / ₂ "	29"	44 ¹ / ₂ "	260 Lbs.	30 Cu Ft	\$ 4,040	<p>Constructed of ³/₄" thick particleboard core back with grade "A" veneer faces which is attached to the end panels by means of hidden key-hole fasteners. The top is fastened to the end panels and back by means beta clips. The unit will accommodate five pull-out shelves operating on blum slides. Shelves will be constructed of ³/₄" thick plywood with grade "A" veneer faces and the front edge banded with a ³/₄" thick x 1³/₄" high solid retainer lip.</p> <p>Sloped top is constructed from ³/₄" thick high density particleboard core. All surfaces of top will have .050" thick laminate. Top will be fitted with a book support rail ⁵/₈" thick x ⁵/₈" deep.</p> <p>End Panel Frame is constructed 1³/₄" thick, consisting of a 1¹/₄" thick 3 ply particleboard core with plain sliced veneer on both faces. Panels are framed on four sides with 1³/₄" thick x 2¹/₂" wide solid hardwood. The top and bottom members overlap the vertical frames. The panel will then be fitted with three ⁵/₈" thick x 2" wide solid vertical pilasters inset with the top and bottom solid frame members. All edges of panel frame and pilasters will be eased.</p> <p>Each leg is fitted with a threaded T-nut to accept a 1¹/₈" diameter cushioned glide with a 1" x ⁵/₁₆" threaded stem.</p>




	MODEL NUMBER	PRODUCT	W	D	H	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
	AP-DC	Dictionary Stand	27 ¹ / ₂ "	21	44 ¹ / ₂ "	180 Lbs.	20 Cu Ft	\$ 3,005	Constructed of ³ / ₄ " thick particleboard core back with grade "A" veneer faces which is attached to the end panels by means of hidden key-hole fasteners. The top is fastened to the end panels and back by means beta clips. The unit complete with one shelf and fixed bottom, constructed of ³ / ₄ " thick plywood with grade "A" veneer faces and the front edge banded with ¹ / ₄ " thick solid hardwood. Shelf is adjustable on 1 ¹ / ₄ " increments. The fixed bottom shelf will have a ³ / ₄ " x 1 ³ / ₄ " drop edge mounted to the front edge.
									Sloped top is constructed from ³ / ₄ " thick high density particleboard core. All surfaces of top will have .050" thick laminate. Top will be fitted with a book support rail ⁵ / ₈ " thick x ⁵ / ₈ " deep.
									End Panel Frame is constructed 1 ³ / ₄ " thick, consisting of a 1 ¹ / ₄ " thick 3 ply particleboard core with plain sliced veneer on both faces. Panels are framed on four sides with 1 ³ / ₄ " thick x 2 ¹ / ₂ " wide solid hardwood. The top and bottom members overlap the vertical frames. The panel will then be fitted with three ⁵ / ₈ " thick x 2" wide solid vertical pilasters inset with the top and bottom solid frame members. All edges of panel frame and pilasters will be eased.
									Each leg is fitted with a threaded T-nut to accept a 1 ¹ / ₈ " diameter cushioned glide with a 1" x ⁵ / ₁₆ " threaded stem.




	MODEL NUMBER	PRODUCT	W	D	H	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
	AP-DP	Display Table	30 ¹ / ₂ "	62 ¹ / ₂ "	39"	245 Lbs.	23 Cu Ft	\$ 6,670	Wood framing constructed from 1 ¹ / ₂ " x 1 ¹ / ₂ " solid hardwood. Framing to be routed to receive 1/4" thick glass on all four sides. Wood framing incorporates glass by means of tongue and groove assembly. All wood edges to be slightly radiused. The back side of the case is equipped with sliding glass doors complete with lock. Case will be fastened to top by means of wood screws.
	AP-DP-FB	Display Table with Fabric Covered Bottom	30 ¹ / ₂ "	62 ¹ / ₂ "	39"	245 Lbs.	23 Cu Ft	\$ 7,335	<p>Display top constructed of 1¹/₄" thick 3 ply particleboard core laminated with a .050" thick high pressure laminate sheet. Bottom surface laminated with a backing sheet not less than .020" thick. The two long edges will have a 3/4" x 1⁵/₈" solid external hardwood edge. Top will have a 1/32" V-groove detail where laminate and solid meet.</p> <p>End Panel Frame is constructed 1³/₄" thick, consisting of a 1¹/₄" thick 3 ply particleboard core with plain sliced veneer on both faces. Panels are framed on four sides with 1³/₄" thick x 2¹/₂" wide solid hardwood. The top and bottom members overlap the vertical frames. The panel will then be fitted with three 5/8" thick x 2" wide solid vertical pilasters inset with the top and bottom solid frame members. All edges of panel frame and pilasters will be eased. Panels will be fastened to top by means of solid hardwood cleats.</p>






MODEL NUMBER	PRODUCT	W	D	H	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
AP-AV	AV Browser	50 ¹ / ₄ "	23	42 ¹ / ₂ "	260 Lbs.	36 Cu Ft	\$ 3,100	<p>MULTIMEDIA DISPLAY BIN: Constructed from ³/₄" thick 3 ply particleboard core with grade "A" face veneer. Storage bin is divided into seven compartments each 6¹/₄" wide complete with six removable black ¹/₄" thick masonite dividers. Bottom of bin will be lined with black ribbed rubber. Bin capacity approximately 290 compact discs. Unit may also accommodate tapes.</p> <p>End Panel Frame is constructed 1³/₄" thick, consisting of a 1¹/₄" thick 3 ply particleboard core with plain sliced veneer on both faces. Panels are framed on four sides with 1³/₄" thick x 2¹/₂" wide solid hardwood. The top and bottom members overlap the vertical frames. The panel will then be fitted with three ⁵/₈" thick x 2" wide solid vertical pilasters inset with the top and bottom solid frame members. All edges of panel frame and pilasters will be eased. Panels will be fastened to top by means of solid hardwood cleats.</p> <p>Each leg is fitted with a threaded T-nut to accept a 1¹/₈" diameter cushioned glide with a 1" x ⁵/₁₆" threaded stem.</p> <p>BOTTOM SUPPORT: Unit will be fitted with a 5" high x 2" thick wood keel. The keel shall be mounted to the underside of the bin and fastened 6¹/₂" above floor by means of hidden keyhole fasteners to end panels.</p>

	MODEL NUMBER	PRODUCT	W	D	H	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
	AP-MC-36-SS	Single Face Modular Carrels: 36" Starter	38 ¹ / ₂ "	31"	48"	340 Lbs.	11 Cu Ft	\$ 3,305	<p>Carrel top shall be constructed of 1¹/₄" thick 3 ply particleboard core. Top surface to be laminated with a .050" thick high pressure laminate sheet, bottom surface laminated with a backing sheet not less than .020" thick for balanced construction. Front edge shall receive a ³/₄" x 1⁵/₈" solid external hardwood edge, top and bottom edges slightly radiused. Edge banded to top after top and bottom laminate sheets have been applied.</p> <p>Top shall be secured to end panels and back by means of machine bolts passing through a 1¹/₂" x 1¹/₂" steel flange into inserts imbedded in the panels. Top will receive a ¹/₃₂" V-groove detail where laminate and solid edge meet. Worksurface 28" deep.</p> <p>END PANEL FRAME ASSEMBLY: End panels shall be constructed 1³/₄" thick, consisting of a 1¹/₄" thick 3 ply particleboard core with plain sliced veneer both faces. Panels are framed on four sides with 1³/₄" thick x 2¹/₂" wide solid hardwood, having the top and bottom members overlapping the vertical frames. The panel will then be fitted with ⁵/₈" thick x 2" wide solid vertical pilasters inset with the top and bottom solid frame members. All edges of panel frame and pilasters will be eased. Single face and pinwheel shall receive 3 vertical pilasters and double face shall receive 5 vertical pilasters.</p> <p>MID PANELS: Intermediate panels shall be constructed from 1¹/₄" thick high density particleboard veneered on both faces with grade "A" veneer. All four edges are banded with 1¹/₄" x 2¹/₂" solid hardwood having top and bottom frame members overlapping the vertical edges. All edges will be eased.</p> <p>BACK PANEL: Constructed from 1" thick particleboard core with plain sliced grade "A" veneer both faces. Top edge is banded with a 1" x 2¹/₄" solid hardwood, edges eased. Back panel will be fastened to end panels by means of hidden key-hole fasteners and pin assembly. Panel will sit 3" above the floor.</p> <p>Each leg is fitted with a threaded T-nut to accept a 1¹/₈" diameter cushioned glide with a 1" x ⁵/₁₆" threaded stem.</p> <p>SHELF: Constructed from ³/₄" thick particleboard core with grade "A" veneer on both faces. Front edge banded with ¹/₄" solid external band, complete with a ³/₄" x 1¹/₂" solid hardwood valence mounted to the underside of the shelf. Shelf is 10" deep positioned 15¹/₂" above the worksurface. Shelf will be mounted to the side panels by means of machine bolts passing through a 1¹/₂" x 1¹/₂" steel flange into inserts imbedded in the end panels.</p> <p>WORKSURFACE: Standard work surface heights shall be 29" high, optional heights of 32" (wheelchair), 27" and 25" may be specified at no additional upcharge.</p>
	AP-MC-36-SA	36" Adder	36 ¹ / ₄ "	31"	48"	160 Lbs.	11 Cu Ft	\$ 2,175	
	AP-MC-48-SS	48" Starter	50 ¹ / ₂ "	31"	48"	360 Lbs.	11 Cu Ft	\$ 3,405	
	AP-MC-48-SA	48" Adder	48 ¹ / ₄ "	31"	48"	190 Lbs.	11 Cu Ft	\$ 2,275	
	AP-MC-36-DS	Double Face Modular Carrels: 36" Starter	38 ¹ / ₂ "	60 ¹ / ₂ "	48"	655 Lbs.	22 Cu Ft	\$ 4,615	
	AP-MC-36-DA	36" Adder	36 ¹ / ₄ "	60 ¹ / ₂ "	48"	250 Lbs.	22 Cu Ft	\$ 2,930	
	AP-MC-48-DS	48" Starter	50 ¹ / ₂ "	60 ¹ / ₂ "	48"	710 Lbs.	22 Cu Ft	\$ 4,755	
	AP-MC-48-DA	48" Adder	48 ¹ / ₄ "	60 ¹ / ₂ "	48"	310 Lbs.	22 Cu Ft	\$ 3,075	
	AP-MC-36-PW	36" Pinwheel	74 ¹ / ₂ "	74 ¹ / ₂ "	48"	780 Lbs.	48 Cu Ft	\$ 7,630	
	AP-MC-48-PW	48" Pinwheel	91 ¹ / ₂ "	91 ¹ / ₂ "	48"	800 Lbs.	55 Cu Ft	\$ 7,900	

	MODEL NUMBER	PRODUCT	W	D	H	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
		Single Face Reference Carrels:							
	AP-RC-36-SS	36" Starter	38 ¹ / ₂ "	31"	48"	340 Lbs.	11 Cu Ft	\$ 3,380	Carrel top shall be constructed of 1 ¹ / ₄ " thick 3 ply particleboard core. Top surface to be laminated with a .050" thick high pressure laminate sheet, bottom surface laminated with a backing sheet not less than .020" thick for balanced construction. Front edge shall receive a ³ / ₄ " x 1 ⁵ / ₈ " solid external hardwood edge, top and bottom edges slightly radiused. Edge banded to top after top and bottom laminate sheets have been applied. Top will be set back from the back panel 2" to provide a wire management drop. Back edge of top will be fitted with a retainer lip. Top shall be secured to end panels and back by means of machine bolts passing through a 1 ¹ / ₂ " x 1 ¹ / ₂ " steel flange into inserts imbedded in the panels. Top will receive a 1 ¹ / ₃₂ " V-groove detail where laminate and solid edge meet.
	AP-RC-36-SA	36" Adder	36 ¹ / ₄ "	31"	48"	160 Lbs.	11 Cu Ft	\$ 2,170	
	AP-RC-48-SS	48" Starter	50 ¹ / ₂ "	31"	48"	360 Lbs.	11 Cu Ft	\$ 3,480	
	AP-RC-48-SA	48" Adder	48 ¹ / ₄ "	31"	48"	190 Lbs.	11 Cu Ft	\$ 2,265	
		Double Face Reference Carrels:							
	AP-RC-36-DS	36" Starter	38 ¹ / ₂ "	60 ¹ / ₂ "	48"	655 Lbs.	22 Cu Ft	\$ 4,605	END PANEL FRAME ASSEMBLY: End panels shall be constructed 1 ³ / ₄ " thick, consisting of a 1 ¹ / ₄ " thick 3 ply particleboard core with plain sliced veneer both faces. Panels are framed on four sides with 1 ³ / ₄ " thick x 2 ¹ / ₂ " wide solid hardwood, having the top and bottom members overlapping the vertical frames. The panel will then be fitted with ⁵ / ₈ " thick x 2" wide solid vertical pilasters inset with the top and bottom solid frame members. All edges of panel frame and pilasters will be eased. Single face and pinwheel shall receive 3 vertical pilasters and double face shall receive 5 vertical pilasters. MID PANELS: Intermediate panels shall be constructed from 1 ¹ / ₄ " thick high density particleboard veneered on both faces with grade "A" veneer. All four edges are banded with 1 ¹ / ₄ " x 2 ¹ / ₂ " solid hardwood having top and bottom frame members overlapping the vertical edges. All edges will be eased. BACK PANEL: Constructed from 1" thick particleboard core with plain sliced grade "A" veneer both faces. Top edge is banded with a 1" x 2 ¹ / ₄ " solid hardwood, edges eased. Back panel will be fastened to end panels by means of hidden key-hole fasteners and pin assembly. Panel will sit 3" above the floor. Each leg is fitted with a threaded T-nut to accept a 1 ¹ / ₈ " diameter cushioned glide with a 1" x ⁵ / ₁₆ " threaded stem. SHELF: Located below the work surface. Constructed from ³ / ₄ " thick particleboard core with grade "A" veneer on both faces. Front edge banded with ¹ / ₄ " solid external band, complete with a ³ / ₄ " x 1 ¹ / ₂ " solid hardwood valence mounted to the underside of the shelf. Shelf is 10" deep positioned 21" above the floor. Shelf will be mounted to the side panels by means of machine bolts passing through a 1 ¹ / ₂ " x 1 ¹ / ₂ " steel flange into inserts imbedded in the end panels. WORKSURFACE: Worksurface 26" deep. Work surface heights adjustable at four increments 39", 32", 29" and 27".
	AP-RC-36-DA	36" Adder	36 ¹ / ₄ "	60 ¹ / ₂ "	48"	250 Lbs.	22 Cu Ft	\$ 2,915	
	AP-RC-48-DS	48" Starter	50 ¹ / ₂ "	60 ¹ / ₂ "	48"	710 Lbs.	22 Cu Ft	\$ 4,740	
	AP-RC-48-DA	48" Adder	48 ¹ / ₄ "	60 ¹ / ₂ "	48"	310 Lbs.	22 Cu Ft	\$ 3,060	
	AP-RC-36-PW	36" Pinwheel	74 ¹ / ₂ "	74 ¹ / ₂ "	48"	780 Lbs.	48 Cu Ft	\$ 7,610	
	AP-RC-48-PW	48" Pinwheel	91 ¹ / ₂ "	91 ¹ / ₂ "	48"	800 Lbs.	55 Cu Ft	\$ 7,710	

	MODEL NUMBER	PRODUCT	W	D	H	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
		1 Person PAC Table:							
	AP-PAC-1-PB-29	Sitting Height	37 ¹ / ₂ "	36"	37"	130 Lbs.	13 Cu Ft	\$ 3,035	SUPERSTRUCTURE: Side panels, back panels and shelves constructed from ³ / ₄ " veneer plywood. All exposed edges of rack banded with ¹ / ₄ " solid external hardwood edge, all edges and corners will be eased. Rack dimensions - ³ / ₄ " thick x 8" high x 7" deep. Rack mounted to top by means of wood screws passing through the underside of the top and into the rack. TOP: Top shall be constructed of 1 ¹ / ₄ " thick 3 ply particleboard core. Top surface to be laminated with a .050" thick high pressure laminate sheet, bottom surface laminated with a backing sheet not less than .020" thick for balanced construction. The two long edges shall receive a ³ / ₄ " x 1 ⁵ / ₈ " solid external hardwood edge. Edges shall be applied to top after the top and bottom laminate sheets have been applied. Top shall receive a ¹ / ₃₂ " V-groove detail where laminate and solid meet. End panels shall be constructed 1 ³ / ₄ " thick, consisting of a 1 ¹ / ₄ " thick 3 ply particleboard core with plain sliced veneer both faces. Panels are framed on four sides with 1 ³ / ₄ " thick x 2 ¹ / ₂ " wide solid hardwood, having the top and bottom members overlapping the vertical frames. The panel will then be fitted with three ⁵ / ₈ " thick x 2" wide solid vertical pilasters inset with the top and bottom solid frame members. All edges of panel frame and pilasters will be eased. Panels will be fastened to top by means of solid hardwood cleats. GLIDES: Each leg will be fitted with a threaded T-nut to accept a 1 ¹ / ₈ " diameter cushioned glide with a 1"x ⁵ / ₁₆ " threaded stem. WORKSURFACE: Standard work surface height shall be 29" high, optional heights of 32" - wheelchair, 27" and 25" may be specified at no additional upcharge. TOP SUPPORT: The top will be fitted with a 6" high x 1" thick wood keel. The keel shall be mounted to the underside of the top and fastened to the end panels by means of wood cleats and screws. ELECTRICAL ACCESSORIES: Each table shall be fitted with 3" diameter black plastic grommets and a black steel wire management channel. The channel will be mounted on the underside of the top towards the back of the unit.
	AP-PAC-1-PB-32	Wheelchair Accessible	37 ¹ / ₂ "	36"	40"	130 Lbs.	16 Cu Ft	\$ 3,120	
	AP-PAC-1-PB-39	Standing Height	37 ¹ / ₂ "	36"	47"	135 Lbs.	23 Cu Ft	\$ 3,300	
		2 Person PAC Table:							
	AP-PAC-2-PB-29	Sitting Height	73 ¹ / ₂ "	36"	37"	200 Lbs.	27 Cu Ft	\$ 3,560	SUPERSTRUCTURE: Side panels, back panels and shelves constructed from ³ / ₄ " veneer plywood. All exposed edges of rack banded with ¹ / ₄ " solid external hardwood edge, all edges and corners will be eased. Rack dimensions - ³ / ₄ " thick x 8" high x 7" deep. Rack mounted to top by means of wood screws passing through the underside of the top and into the rack. TOP: Top shall be constructed of 1 ¹ / ₄ " thick 3 ply particleboard core. Top surface to be laminated with a .050" thick high pressure laminate sheet, bottom surface laminated with a backing sheet not less than .020" thick for balanced construction. The two long edges shall receive a ³ / ₄ " x 1 ⁵ / ₈ " solid external hardwood edge. Edges shall be applied to top after the top and bottom laminate sheets have been applied. Top shall receive a ¹ / ₃₂ " V-groove detail where laminate and solid meet. End panels shall be constructed 1 ³ / ₄ " thick, consisting of a 1 ¹ / ₄ " thick 3 ply particleboard core with plain sliced veneer both faces. Panels are framed on four sides with 1 ³ / ₄ " thick x 2 ¹ / ₂ " wide solid hardwood, having the top and bottom members overlapping the vertical frames. The panel will then be fitted with three ⁵ / ₈ " thick x 2" wide solid vertical pilasters inset with the top and bottom solid frame members. All edges of panel frame and pilasters will be eased. Panels will be fastened to top by means of solid hardwood cleats. GLIDES: Each leg will be fitted with a threaded T-nut to accept a 1 ¹ / ₈ " diameter cushioned glide with a 1"x ⁵ / ₁₆ " threaded stem. WORKSURFACE: Standard work surface height shall be 29" high, optional heights of 32" - wheelchair, 27" and 25" may be specified at no additional upcharge. TOP SUPPORT: The top will be fitted with a 6" high x 1" thick wood keel. The keel shall be mounted to the underside of the top and fastened to the end panels by means of wood cleats and screws. ELECTRICAL ACCESSORIES: Each table shall be fitted with 3" diameter black plastic grommets and a black steel wire management channel. The channel will be mounted on the underside of the top towards the back of the unit.
	AP-PAC-2-PB-32	Wheelchair Accessible	73 ¹ / ₂ "	36"	40"	200 Lbs.	33 Cu Ft	\$ 3,650	
	AP-PAC-2-PB-39	Standing Height	73 ¹ / ₂ "	36"	47"	205 Lbs.	46 Cu Ft	\$ 3,810	
		3 Person PAC Table:							
	AP-PAC-3-PB-29	Sitting Height	91 ¹ / ₂ "	36"	37"	250 Lbs.	34 Cu Ft	\$ 3,915	SUPERSTRUCTURE: Side panels, back panels and shelves constructed from ³ / ₄ " veneer plywood. All exposed edges of rack banded with ¹ / ₄ " solid external hardwood edge, all edges and corners will be eased. Rack dimensions - ³ / ₄ " thick x 8" high x 7" deep. Rack mounted to top by means of wood screws passing through the underside of the top and into the rack. TOP: Top shall be constructed of 1 ¹ / ₄ " thick 3 ply particleboard core. Top surface to be laminated with a .050" thick high pressure laminate sheet, bottom surface laminated with a backing sheet not less than .020" thick for balanced construction. The two long edges shall receive a ³ / ₄ " x 1 ⁵ / ₈ " solid external hardwood edge. Edges shall be applied to top after the top and bottom laminate sheets have been applied. Top shall receive a ¹ / ₃₂ " V-groove detail where laminate and solid meet. End panels shall be constructed 1 ³ / ₄ " thick, consisting of a 1 ¹ / ₄ " thick 3 ply particleboard core with plain sliced veneer both faces. Panels are framed on four sides with 1 ³ / ₄ " thick x 2 ¹ / ₂ " wide solid hardwood, having the top and bottom members overlapping the vertical frames. The panel will then be fitted with three ⁵ / ₈ " thick x 2" wide solid vertical pilasters inset with the top and bottom solid frame members. All edges of panel frame and pilasters will be eased. Panels will be fastened to top by means of solid hardwood cleats. GLIDES: Each leg will be fitted with a threaded T-nut to accept a 1 ¹ / ₈ " diameter cushioned glide with a 1"x ⁵ / ₁₆ " threaded stem. WORKSURFACE: Standard work surface height shall be 29" high, optional heights of 32" - wheelchair, 27" and 25" may be specified at no additional upcharge. TOP SUPPORT: The top will be fitted with a 6" high x 1" thick wood keel. The keel shall be mounted to the underside of the top and fastened to the end panels by means of wood cleats and screws. ELECTRICAL ACCESSORIES: Each table shall be fitted with 3" diameter black plastic grommets and a black steel wire management channel. The channel will be mounted on the underside of the top towards the back of the unit.
	AP-PAC-3-PB-32	Wheelchair Accessible	91 ¹ / ₂ "	36"	40"	250 Lbs.	41 Cu Ft	\$ 3,995	
	AP-PAC-3-PB-39	Standing Height	91 ¹ / ₂ "	36"	47"	260 Lbs.	58 Cu Ft	\$ 4,165	

	MODEL NUMBER	PRODUCT	W	D	H	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
	AP-R42	Round Table	42"	42"	29"	90 Lbs.	8 Cu Ft	\$ 1,810	<p>PANEL FRAME ASSEMBLY: End panel frames constructed from two 2¹/₂" x 1¹/₄" horizontal rails, two 2¹/₂" square glued-up solid stock legs and five 1⁷/₈" x ³/₄" vertical hardwood pilasters. Top and bottom horizontal rails shall be doweled and glued to legs, vertical pilasters shall also be doweled and glued to top and bottom rails.</p> <p>APRON: A solid apron rail 2¹/₂" x 1¹/₄" shall be fitted between the legs on either side of the panel frame assemblies. The apron will be inset from the table top ¹/₈". Apron rail will be mechanically fastened to the end frame and attached to the underside of the table top by means of metal brackets.</p>
	AP-R48		48"	48"	29"	100 Lbs.	10 Cu Ft	\$ 1,900	
	AP-4242	Square Table	42"	42"	29"	90 Lbs.	8 Cu Ft	\$ 2,295	<p>TABLE TOP: Table tops shall be constructed of 1¹/₄" thick 3 ply particleboard core. Top surface to be laminated with a .050" thick high pressure plastic laminate sheet, bottom surface laminated with a backing sheet not less than .020" thick for balanced construction. The two long edges of rectangular tables will be banded with a ³/₈" x 1¹/₄" solid hardwood external edge. The two shorter edges will receive a 2³/₄" x 1¹/₄" solid hardwood edge, all edges will be slightly radiused. Circular tables will be banded with a ¹/₄" x 1¹/₄" solid hardwood external edge band. Square tables will be banded on 4 sides with 2³/₄" x 1¹/₄" solid hardwood external edge band.</p>
	AP-4848		48"	48"	29"	100 Lbs.	10 Cu Ft	\$ 2,450	
	AP-6036	60" Wide Rectangular Table	60"	36"	29"			\$ 3,035	<p>TABLE TOP SUPPORTS: All tables 60" and longer shall be fitted with a V-shaped, 14 gauge steel keel. The keel shall be mounted to the underside of the top by means of wood screws. All tables 48" wide and 60" long and longer shall be fitted with two parallel running steel keels.</p> <p>GLIDES: Each leg will be fitted with a threaded T-nut to accept a 1⁵/₈" diameter cushioned glide with a 1¹/₂" x ³/₈" threaded stem.</p> <p>WORKSURFACE HEIGHT: Standard work surface height shall be 29" h. Optional heights of 32" - wheelchair, 27" and 25" may be specified at no additional upcharge.</p> <p>OPTION: Solid lumber core top</p>
	AP-6048		60"	48"	29"			\$ 3,255	
	AP-7236	72" Wide Rectangular Table	72"	36"	29"			\$ 3,175	
	AP-7248		72"	48"	29"			\$ 3,405	
	AP-8436	84" Wide Rectangular Table	84"	36"	29"			\$ 3,310	
	AP-8448		84"	48"	29"			\$ 3,555	
	AP-9636	96" Wide Rectangular Table	96"	36"	29"			\$ 3,455	
	AP-9648		96"	48"	29"			\$ 3,700	