

	MODEL NUMBER	PRODUCT	WIDTH	DEPTH	HEIGHT	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
	LG-T-AC-STC LG-T-SQ-STC	Table Pod Acrylic Edge Square Edge	47 1/2"	24"	29"	23 Lbs.	19.5 Cu Ft	\$ 800 \$ 830	<p>Small and Large Table Pods connect to the Center Pod to create workstations. The Pods connect on a swivel hinge allowing them to be easily adjusted to endless different user configurations.</p> <p>An optional Power Sphere connects into the top middle of the Center Pod which can supply four power outlets or two power and two data outlets.</p> <p>There are two edge profiles available:</p> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;">  <p>Model "AC" 3mm Vinyl Acrylic Edge</p> </div> <div style="text-align: center;">  <p>Model "SQ" 1/8" Square Edge</p> </div> </div>
	LG-L-AC-STC LG-L-SQ-STC	Large Table Pod Acrylic Edge Square Edge	34 1/4"	34 1/4"	29"	31 Lbs.	20 Cu Ft	\$ 970 \$ 1,010	
	LG-CP4-AC LG-CP4-SQ	Center Pod: Quad Acrylic Edge Square Edge	28 1/2"	28 1/2"	27 1/2"	105 Lbs.	13 Cu Ft	\$ 1,355 \$ 1,385	 <p>Model "STC" Straight Caster Leg</p>
	LG-CP3-AC LG-CP3-SQ	Center Pod: Triple Acrylic Edge Square Edge	28 1/2"	28 1/2"	27 1/2"	_____ Lbs.	_____ Cu Ft	\$ 1,320 \$ 1,345	



CONFIGURATION A: TRIPLE WORKSTATION

LG-CA-AC-STC	Acrylic Edge, Straight Caster	\$ 3,720
LG-CA-SQ-STC	Square Edge, Straight Caster	\$ 3,835



CONFIGURATION C: TRIPLE WORKSTATION,
1 LARGE & 2 SMALL PODS

LG-CC-AC-STC	Acrylic Edge, Straight Caster	\$ 3,890
LG-CC-SQ-STC	Square Edge, Straight Caster	\$ 4,015




CONFIGURATION B: QUAD WORKSTATION

LG-CB-AC-STC	Acrylic Edge, Straight Caster	\$ 4,555
LG-CB-SQ-STC	Square Edge, Straight Caster	\$ 4,705



CONFIGURATION D: QUAD WORKSTATION,
2 LARGE & 2 SMALL PODS

LG-CD-AC-STC	Acrylic Edge, Straight Caster	\$ 4,895
LG-CD-SQ-STC	Square Edge, Straight Caster	\$ 5,065

	MODEL NUMBER	PRODUCT	WIDTH	DEPTH	HEIGHT	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
	S-FA-S	Frosted Acrylic Screen - Small	20"		8"	2.5 Lbs.	0.5 Cu Ft	\$ 265	
	S-FA-L	Frosted Acrylic Screen - Large	32"		8"	2.5 Lbs.	0.5 Cu Ft	\$ 280	
	S-FAS	Frosted Acrylic Screen Surround	32"	13"	8"	9.5 Lbs.	0.5 Cu Ft	\$ 545	
	S-WS	Wood Screen Surround	32"	7"	8"	8 Lbs. 8 Lbs.	0.5 Cu Ft 0.5 Cu Ft	\$ 270	
	S-SWM-S	Wood Frame Perforated Metal Screen Small	20"		8"			\$ 500	
	S-SWM-L	Wood Frame Perforated Metal Screen Large	32"		16"			\$ 745	
	S-SWW-S	Wood Screen, Metal Posts Small	20"		8"			\$ 330	
	S-SWW-L	Wood Screen, Metal Posts Large	32"		16"			\$ 495	
	S-SWA	Wood Frame, Metal Posts, Frosted Acrylic Screen	24"		16"			\$ 745	

	MODEL NUMBER	PRODUCT	WIDTH	DEPTH	HEIGHT	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
	PD-BL	Pencil Drawer	20 ⁷ / ₈ "	18 ¹ / ₂ "	1 ⁷ / ₈ "	__ Lbs.	__ Cu Ft	\$ 140	Pencil & paper drawer. Includes roller slides and frame for under-desk mounting. Black finish.
	CD-250-PK	Pullout Keyboard	24"	11"		__ Lbs.	__ Cu Ft	\$ 510	
	CD-250-AK	Articulating Keyboard and Mouse	21"	10"		__ Lbs.	__ Cu Ft	\$ 510	
	PW-G2D	Plastic Grommet 2"	2"	2"	³ / ₄ "	0.1 Lbs.	__ Cu Ft	\$ 85	
	PW-G3D	Plastic Grommet 3"	3"	3"	³ / ₄ "			\$ 85	
	P-TC-V	Vertical Flex Wire Leg	3"	2"	32 ¹ / ₂ "	__ Lbs.	__ Cu Ft	\$ 165	32 ¹ / ₂ " Silver Plastic. Separates wire in different channels for easier maintenance. Kit includes: 1 top bracket, 15 spine wheels, 2 fixing clips for horizontal applications and 1 weighted base. Also comes in Black.
	P-TC	Table Connector	3"	2"		__ Lbs.	__ Cu Ft	\$ 40	
	PW-OWMT-30	Wire Manager	30"	2"		__ Lbs.	__ Cu Ft	\$ 85	

	MODEL NUMBER	PRODUCT	WIDTH	DEPTH	HEIGHT	WEIGHT	VOLUME	LIST PRICE	DESCRIPTION
	PW-100-F	Flip-Up Power - 2 outlet, 2 data	9"		5 1/2"	___ Lbs.	___ Cu Ft	\$ 625	Black Metal
	PW-100-J	Jr. Flip-Up Power - 2 outlet, 2 data	5 3/4"		5 1/2"	___ Lbs.	___ Cu Ft	\$ 505	Black Metal
	DTP-BL	Desktop Power and Data	7"		3"	___ Lbs.	___ Cu Ft	\$ 230	Black Plastic
	P-PS-B	Power Sphere - 4 outlets - Black	3"		3"	___ Lbs.	___ Cu Ft	\$ 275	Black Plastic
	P-PDS-B	Power Sphere - 2 outlets, 2 data - Black	3"		3"	___ Lbs.	___ Cu Ft	\$ 215	
	P-PS-T	Power Sphere - 4 outlets - Translucent	3"		3"	___ Lbs.	___ Cu Ft	\$ 275	Translucent Plastic
	P-PDS-T	Power Sphere - 2 outlets, 2 data - Translucent	3"		3"	___ Lbs.	___ Cu Ft	\$ 215	
	PW-SPC-6	6 Outlet Power Bar	11"		2"	___ Lbs.	___ Cu Ft	\$ 125	White Plastic - 15 amp 120V

WOODS & FINISHES:

Natural Maple Standard



Natural Clear – M-NA

Maple Finishes

The following stains are available, add 10% to list



Honey Oak – M-HO



Castle Oak – M-CO



Richmond Cherry – M-RC



Mahogany – M-MA



Victorian Cherry – M-VI



Java – M-JA



Wenge – M-WE



English Oak – M-EN

Natural Red Oak Standard



Natural Clear – O-NA

Red Oak Finishes

The following stains are available, add 10% to list



Castle Oak – O-CO



Honey Oak – O-HO



English Oak – O-EN



Victorian Cherry – O-VI



Mahogany – O-MA



Richmond Cherry – O-RC



Java – O-JA



Wenge – O-WE

Natural Cherry Add 20% to list



Natural Clear – C-NA

Cherry Finishes

The following stains are available, add 30% to list



Honey Oak – C-HO



Richmond Cherry – C-RC

Natural Walnut Add 20% to list



Natural Clear – W-NA

Walnut Finishes

The following stain is available, add 30% to list



Java – W-JA

LAMINATES:

Melamine Laminate Options



Hardrock Maple – L303



Fidlar's Maple – L363



Cognac Cherry – L448



Cherry Blossom – L449



Almond Cherry – L457



Samba Cherry – L460



Lambada Cherry – L461



Shiraz Cherry – L472



Tuxedo – 477



Hot Cinnamon – L480



Caramel Maple – L490



Antigua – L498



Borneo – L500



Ginger Snap Fruitwood – L518



Very Chic – L666

METAL THERMAL PAINT COLOURS:



Sparkle Silver – S11



Navy – B17



Charcoal – A230



Beige – H23



Blue – B11



Grey – A16




Antique White – W11



Teal – HG266



Black – N49



White – PS-111-W374



Green – G58



Black Sandtex – N31
Textured Finish



Ruby – R7

HARDWOODS: All hardwood materials used in the manufacturing of P2 products shall be Northern grown hardwoods. Hardwoods will be air and kiln dried to a moisture content of 5-7%. All hardwoods shall be of grade "A" material, free of material stains, imperfections, conformity of grain, texture and color. Hardwood species shall be Northern grown Red Oak, Clear White Northern Maple and Birch. American Cherry and Honduras Mahogany and Walnut are available. Please inquire for pricing.

VENEER: Exposed face veneers shall be not less than 1/28" thick plain sliced veneers. Veneers are to be selected for conformity of grain direction and color. Veneers are to be stitched tightly in a book match, slip match or plain sliced configuration. Unexposed veneers are to be of hardwood but not selected for color, or grain quality. Veneers are not to be lap joined or reveal any tape or glue lines.

PARTICLE BOARD CORE: The particleboard shall be formed of wood chips, bonded with a water resistance adhesive. The particleboard material is to be of a high density 45 lbs/cu. ft. having a minimum average modules of rupture of 2400 psi and a minimum average modules of elasticity of 4,000,000 psi.

VENEER CORE: Veneer core is to be constructed with odd numbers of plies. Each ply is to be laminated in pairs and cross banded in opposite directions with grain direction at a 90 degree angle to the grain of the center core. All plies are to be free from knots, wrinkles, laps or other natural or manufacturing defects.

HIGH PRESSURE LAMINATE: Work surface laminate shall be .050" thick and used with balancing backer sheet of no less than .028" thick. Laminate shall conform to standards set by the National Electrical Manufacturers' Association (NEMA).

FINISHING PROCEDURES: All materials shall be inspected and treated with a final sanding and polishing operation before any staining and final finishing can be performed. All machine and mill marks are to be removed. Once the polishing and sanding has been performed, the furniture will then undergo the following stain and finishing procedures:

Step 1: A base stain will be uniformly applied, wiped and then allowed to dry under factory controlled conditions.

Step 2: A uniform coat of sealer will be applied and allowed to dry.

Step 3: Sealer will be lightly sanded using 240 grit silicon paper.

Step 4: A catalytic lacquer of 34-45 degree sheen is evenly applied and allowed to dry under factory controlled conditions.

METAL FINISHING PROCEDURES: All metal components are thoroughly cleaned and coated electrostatically with an epoxy powder coat paint finish. The metal components are then oven baked and cured for a lasting finish.